Chain sling 2-leg with latch hook, grade 8

Product information



2-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 °C up to +200°C
Finish: Painted, black / yellow
Standard: EN 818-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Chain sling 2-leg with latch hook, grade 8

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
230800600100110	6	1.6	1	6.61
230800600200110	6	1.6	2	9.44
230800600300110	6	1.6	3	12.27
230800600400110	6	1.6	4	15.1
230800600500110	6	1.6	5	17.93
230800600600110	6	1.6	6	20.76
230800600700110	6	1.6	7	23.59
230800600800110	6	1.6	8	26.42
230800800100110	8	2.8	1	6.61
230800800200110	8	2.8	2	9.44
230800800300110	8	2.8	3	12.27
230800800400110	8	2.8	4	15.1
230800800500110	8	2.8	5	17.93
230800800600110	8	2.8	6	20.76
230800800700110	8	2.8	7	23.59
230800800800110	8	2.8	8	26.42
230801000100110	10	4.25	1	10.49
230801000200110	10	4.25	2	14.92
230801000300110	10	4.25	3	19.35
230801000400110	10	4.25	4	23.78
230801000500110	10	4.25	5	28.21
230801000600110	10	4.25	6	32.64
230801000700110	10	4.25	7	37.07
230801000800110	10	4.25	8	41.5
230801300100110	13	7.5	1	18.62
230801300200110	13	7.5	2	26.12
230801300300110	13	7.5	3	33.62
230801300400110	13	7.5	4	41.12
230801300500110	13	7.5	5	48.62
230801300600110	13	7.5	6	56.12
230801300700110	13	7.5	7	63.62

© November 2026 - All Rights Reserved

Chain sling 2-leg with latch hook, grade 8

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
230801300800110	13	7.5	8	71.12
230801600200110	16	11.2	2	42.26
230801600300110	16	11.2	3	53.4
230801600400110	16	11.2	4	64.54
230801600500110	16	11.2	5	75.68
230801600600110	16	11.2	6	86.82
230801600700110	16	11.2	7	97.96
230801600800110	16	11.2	8	109.1
230802000200110	20	17	2	70.1
230802000300110	20	17	3	88.3
230802000400110	20	17	4	106.5
230802000500110	20	17	5	124.7
230802000600110	20	17	6	142.9
230802000700110	20	17	7	161.1
230802000800110	20	17	8	179.3
230802200200110	22	21.2	2	105.7
230802200300110	22	21.2	3	127.7
230802200400110	22	21.2	4	149.7
230802200500110	22	21.2	5	171.7
230802200600110	22	21.2	6	193.7
230802200700110	22	21.2	7	215.7
230802200800110	22	21.2	8	237.7
230802600200110	26	30	2	141.4
230802600300110	26	30	3	172
230802600400110	26	30	4	202.6
230802600500110	26	30	5	233.2
230802600600110	26	30	6	263.8
230802600700110	26	30	7	294.4
230802600800110	26	30	8	325

© November 2026 - All Rights Reserved