



## Chain sling 4-leg with safety hook, grade 8

### Product information

4-legs chain sling assembly equipped with safety hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

| Part code       | Chain diameter<br>mm | WLL<br>ton | EWL<br>m | Weight<br>kg |
|-----------------|----------------------|------------|----------|--------------|
| 231300600100140 | 6                    | 2.36       | 1        | 13.46        |
| 231300600200140 | 6                    | 2.36       | 2        | 19.13        |
| 231300600300140 | 6                    | 2.36       | 3        | 24.8         |
| 231300600400140 | 6                    | 2.36       | 4        | 30.46        |
| 231300600500140 | 6                    | 2.36       | 5        | 36.13        |
| 231300600600140 | 6                    | 2.36       | 6        | 41.8         |
| 231300600700140 | 6                    | 2.36       | 7        | 47.47        |

|                 |    |      |   |        |
|-----------------|----|------|---|--------|
| 231300600800140 | 6  | 2.36 | 8 | 53.14  |
| 231300800100140 | 8  | 4.25 | 1 | 13.46  |
| 231300800200140 | 8  | 4.25 | 2 | 19.13  |
| 231300800300140 | 8  | 4.25 | 3 | 24.8   |
| 231300800400140 | 8  | 4.25 | 4 | 30.46  |
| 231300800500140 | 8  | 4.25 | 5 | 36.13  |
| 231300800600140 | 8  | 4.25 | 6 | 41.8   |
| 231300800700140 | 8  | 4.25 | 7 | 47.47  |
| 231300800800140 | 8  | 4.25 | 8 | 53.14  |
| 231301000100140 | 10 | 6.7  | 1 | 22.42  |
| 231301000200140 | 10 | 6.7  | 2 | 31.28  |
| 231301000300140 | 10 | 6.7  | 3 | 40.14  |
| 231301000400140 | 10 | 6.7  | 4 | 49     |
| 231301000500140 | 10 | 6.7  | 5 | 57.86  |
| 231301000600140 | 10 | 6.7  | 6 | 66.72  |
| 231301000700140 | 10 | 6.7  | 7 | 75.58  |
| 231301000800140 | 10 | 6.7  | 8 | 84.44  |
| 231301300200140 | 13 | 11.2 | 2 | 57.58  |
| 231301300300140 | 13 | 11.2 | 3 | 72.58  |
| 231301300400140 | 13 | 11.2 | 4 | 87.58  |
| 231301300500140 | 13 | 11.2 | 5 | 102.58 |
| 231301300600140 | 13 | 11.2 | 6 | 117.58 |
| 231301300700140 | 13 | 11.2 | 7 | 132.58 |

|                 |    |      |   |        |
|-----------------|----|------|---|--------|
| 231301300800140 | 13 | 11.2 | 8 | 147.58 |
| 231301600200140 | 16 | 17   | 2 | 93.04  |
| 231301600300140 | 16 | 17   | 3 | 115.32 |
| 231301600400140 | 16 | 17   | 4 | 137.6  |
| 231301600500140 | 16 | 17   | 5 | 159.88 |
| 231301600600140 | 16 | 17   | 6 | 182.16 |
| 231301600700140 | 16 | 17   | 7 | 204.44 |
| 231301600800140 | 16 | 17   | 8 | 226.72 |
| 231302000200140 | 20 | 26.5 | 2 | 149.3  |
| 231302000300140 | 20 | 26.5 | 3 | 185.7  |
| 231302000400140 | 20 | 26.5 | 4 | 222.1  |
| 231302000500140 | 20 | 26.5 | 5 | 258.5  |
| 231302000600140 | 20 | 26.5 | 6 | 294.9  |
| 231302000700140 | 20 | 26.5 | 7 | 331.3  |
| 231302000800140 | 20 | 26.5 | 8 | 367.7  |
| 231302200200140 | 22 | 31.5 | 2 | 214    |
| 231302200300140 | 22 | 31.5 | 3 | 258    |
| 231302200400140 | 22 | 31.5 | 4 | 302    |
| 231302200500140 | 22 | 31.5 | 5 | 346    |
| 231302200600140 | 22 | 31.5 | 6 | 390    |
| 231302200700140 | 22 | 31.5 | 7 | 434    |
| 231302200800140 | 22 | 31.5 | 8 | 478    |
| 231302600200140 | 26 | 45   | 2 | 279.4  |

|                 |    |    |   |       |
|-----------------|----|----|---|-------|
| 231302600300140 | 26 | 45 | 3 | 340.6 |
| 231302600400140 | 26 | 45 | 4 | 401.8 |
| 231302600500140 | 26 | 45 | 5 | 463   |
| 231302600600140 | 26 | 45 | 6 | 524.2 |
| 231302600700140 | 26 | 45 | 7 | 585.4 |
| 231302600800140 | 26 | 45 | 8 | 646.6 |