

## Chain sling 4-leg with latch hook, grade 8

### Product information



4-legs chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Chain sling 4-leg with latch hook, grade 8

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
231300600100120	6	2.36	1	13.79
231300600200120	6	2.36	2	19.46
231300600300120	6	2.36	3	25.12
231300600400120	6	2.36	4	30.79
231300600500120	6	2.36	5	36.46
231300600600120	6	2.36	6	42.13
231300600700120	6	2.36	7	47.8
231300600800120	6	2.36	8	53.47
231300800100120	8	4.25	1	13.79
231300800200120	8	4.25	2	19.46
231300800300120	8	4.25	3	25.12
231300800400120	8	4.25	4	30.79
231300800500120	8	4.25	5	36.46
231300800600120	8	4.25	6	42.13
231300800700120	8	4.25	7	47.8
231300800800120	8	4.25	8	53.47
231301000100120	10	6.7	1	21.38
231301000200120	10	6.7	2	30.24
231301000300120	10	6.7	3	39.1
231301000400120	10	6.7	4	47.96
231301000500120	10	6.7	5	56.82
231301000600120	10	6.7	6	65.68
231301000700120	10	6.7	7	74.54
231301000800120	10	6.7	8	83.4
231301300200120	13	11.2	2	53.7
231301300300120	13	11.2	3	68.7
231301300400120	13	11.2	4	83.7
231301300500120	13	11.2	5	98.7
231301300600120	13	11.2	6	113.7
231301300700120	13	11.2	7	128.7
231301300800120	13	11.2	8	143.7

## Chain sling 4-leg with latch hook, grade 8

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
231301600200120	16	17	2	86.92
231301600300120	16	17	3	109.2
231301600400120	16	17	4	131.48
231301600500120	16	17	5	153.76
231301600600120	16	17	6	176.04
231301600700120	16	17	7	198.32
231301600800120	16	17	8	220.6
231302000200120	20	26.5	2	149.3
231302000300120	20	26.5	3	185.7
231302000400120	20	26.5	4	222.1
231302000500120	20	26.5	5	258.5
231302000600120	20	26.5	6	294.9
231302000700120	20	26.5	7	331.3
231302000800120	20	26.5	8	367.7
231302200200120	22	31.5	2	214
231302200300120	22	31.5	3	258
231302200400120	22	31.5	4	302
231302200500120	22	31.5	5	346
231302200600120	22	31.5	6	390
231302200700120	22	31.5	7	434
231302200800120	22	31.5	8	478
231302600200120	26	45	2	279.4
231302600300120	26	45	3	340.6
231302600400120	26	45	4	401.8
231302600500120	26	45	5	463
231302600600120	26	45	6	524.2
231302600700120	26	45	7	585.4
231302600800120	26	45	8	646.6