


Chain sling 2-leg with latch hook, grade 10

Product information



2-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

Material: Steel

Marking: CE-marked

Temperature range: -40 °C up to +200°C

Finish: Painted

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 10

Chain sling 2-leg with latch hook, grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
240800600100180	6	2	1	5.86
240800600200180	6	2	2	8.86
240800600300180	6	2	3	11.86
240800600400180	6	2	4	14.86
240800600500180	6	2	5	17.86
240800600600180	6	2	6	20.86
240800600700180	6	2	7	23.86
240800600800180	6	2	8	26.86
240800800100180	8	3.55	1	5.86
240800800200180	8	3.55	2	8.86
240800800300180	8	3.55	3	11.86
240800800400180	8	3.55	4	14.86
240800800500180	8	3.55	5	17.86
240800800600180	8	3.55	6	20.86
240800800700180	8	3.55	7	23.86
240800800800180	8	3.55	8	26.86
240801000100180	10	5.6	1	10.76
240801000200180	10	5.6	2	15.36
240801000300180	10	5.6	3	19.96
240801000400180	10	5.6	4	24.56
240801000500180	10	5.6	5	29.16
240801000600180	10	5.6	6	33.76
240801000700180	10	5.6	7	38.36
240801000800180	10	5.6	8	42.96
240801300100180	13	9.5	1	19.7
240801300200180	13	9.5	2	27.5
240801300300180	13	9.5	3	35.3
240801300400180	13	9.5	4	43.1
240801300500180	13	9.5	5	50.9
240801300600180	13	9.5	6	58.7
240801300700180	13	9.5	7	66.5

Chain sling 2-leg with latch hook, grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
240801300800180	13	9.5	8	74.3
240801600200180	16	14	2	45.12
240801600300180	16	14	3	56.72
240801600400180	16	14	4	68.32
240801600500180	16	14	5	79.92
240801600600180	16	14	6	91.52
240801600700180	16	14	7	103.12
240801600800180	16	14	8	114.72
240802000200180	20	22.4	2	70.1
240802000300180	20	22.4	3	88.3
240802000400180	20	22.4	4	106.5
240802000500180	20	22.4	5	124.7
240802000600180	20	22.4	6	142.9
240802000700180	20	22.4	7	161.1
240802000800180	20	22.4	8	179.3
240802200200180	22	26.5	2	105.7
240802200300180	22	26.5	3	127.7
240802200400180	22	26.5	4	149.7
240802200500180	22	26.5	5	171.7
240802200600180	22	26.5	6	193.7
240802200700180	22	26.5	7	215.7
240802200800180	22	26.5	8	237.7
240802600200180	26	37.5	2	141.4
240802600300180	26	37.5	3	172
240802600400180	26	37.5	4	202.6
240802600500180	26	37.5	5	233.2
240802600600180	26	37.5	6	263.8
240802600700180	26	37.5	7	294.4
240802600800180	26	37.5	8	325