

## Chain sling 4-leg with latch hook, grade 10

---

### Product information



4-Leg chain sling assembly equipped with latch hooks and grab hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

---

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

## Chain sling 4-leg with latch hook, grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
241300600100200	6	3	1	12.52
241300600200200	6	3	2	18.52
241300600300200	6	3	3	24.52
241300600400200	6	3	4	30.52
241300600500200	6	3	5	36.52
241300600600200	6	3	6	42.52
241300600700200	6	3	7	48.52
241300600800200	6	3	8	54.52
241300800100200	8	5.3	1	12.52
241300800200200	8	5.3	2	18.52
241300800300200	8	5.3	3	24.52
241300800400200	8	5.3	4	30.52
241300800500200	8	5.3	5	36.52
241300800600200	8	5.3	6	42.52
241300800700200	8	5.3	7	48.52
241300800800200	8	5.3	8	54.52
241301000100200	10	8.4	1	22.12
241301000200200	10	8.4	2	31.32
241301000300200	10	8.4	3	40.52
241301000400200	10	8.4	4	49.72
241301000500200	10	8.4	5	58.92
241301000600200	10	8.4	6	68.12
241301000700200	10	8.4	7	77.32
241301000800200	10	8.4	8	86.52
241301300200200	13	14	2	56.2
241301300300200	13	14	3	71.8
241301300400200	13	14	4	87.4
241301300500200	13	14	5	103
241301300600200	13	14	6	118.6
241301300700200	13	14	7	134.2
241301300800200	13	14	8	149.8

## Chain sling 4-leg with latch hook, grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
241301600200200	16	21.2	2	88.04
241301600300200	16	21.2	3	111.24
241301600400200	16	21.2	4	134.44
241301600500200	16	21.2	5	157.64
241301600600200	16	21.2	6	180.84
241301600700200	16	21.2	7	204.04
241301600800200	16	21.2	8	227.24
241302000200200	20	33.6	2	149.3
241302000300200	20	33.6	3	185.7
241302000400200	20	33.6	4	222.1
241302000500200	20	33.6	5	258.5
241302000600200	20	33.6	6	294.9
241302000700200	20	33.6	7	331.3
241302000800200	20	33.6	8	367.7
241302200200200	22	40	2	214
241302200300200	22	40	3	258
241302200400200	22	40	4	302
241302200500200	22	40	5	346
241302200600200	22	40	6	390
241302200700200	22	40	7	434
241302200800200	22	40	8	478
241302600200200	26	56	2	279.4
241302600300200	26	56	3	340.6
241302600400200	26	56	4	401.8
241302600500200	26	56	5	463
241302600600200	26	56	6	524.2
241302600700200	26	56	7	585.4
241302600800200	26	56	8	646.6