

## Chain sling 1-leg with swivel ball bearing safety hook, grade 10

---

### Product information



1-Leg chain sling assembly equipped with swivel ball bearing hook and grab hook. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

... [Read more](#)

---

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 °C up to +200°C

**Finish:** Painted

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 10

## Chain sling 1-leg with swivel ball bearing safety hook, grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
240500600100230	6	1.4	1	3.77
240500600200230	6	1.4	2	5.27
240500600300230	6	1.4	3	6.77
240500600400230	6	1.4	4	8.27
240500600500230	6	1.4	5	9.77
240500600600230	6	1.4	6	11.27
240500600700230	6	1.4	7	12.77
240500600800230	6	1.4	8	14.27
240500800100230	8	2.5	1	3.77
240500800200230	8	2.5	2	5.27
240500800300230	8	2.5	3	6.77
240500800400230	8	2.5	4	8.27
240500800500230	8	2.5	5	9.77
240500800600230	8	2.5	6	11.27
240500800700230	8	2.5	7	12.77
240500800800230	8	2.5	8	14.27
240501000100230	10	4	1	6.67
240501000200230	10	4	2	8.97
240501000300230	10	4	3	11.27
240501000400230	10	4	4	13.57
240501000500230	10	4	5	15.87
240501000600230	10	4	6	18.17
240501000700230	10	4	7	20.47
240501000800230	10	4	8	22.77
240501300100230	13	6.7	1	12.83
240501300200230	13	6.7	2	16.73
240501300300230	13	6.7	3	20.63
240501300400230	13	6.7	4	24.53
240501300500230	13	6.7	5	28.43
240501300600230	13	6.7	6	32.33
240501300700230	13	6.7	7	36.23

## Chain sling 1-leg with swivel ball bearing safety hook, grade 10

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
240501300800230	13	6.7	8	40.13
240501600100230	16	10	1	21.08
240501600200230	16	10	2	26.88
240501600300230	16	10	3	32.68
240501600400230	16	10	4	38.48
240501600500230	16	10	5	44.28
240501600600230	16	10	6	50.08
240501600700230	16	10	7	55.88
240501600800230	16	10	8	61.68
240502000200230	20	16	2	37.4
240502000300230	20	16	3	46.5
240502000400230	20	16	4	55.6
240502000500230	20	16	5	64.7
240502000600230	20	16	6	73.8
240502000700230	20	16	7	82.9
240502000800230	20	16	8	92
240502200200230	22	19	2	55.4
240502200300230	22	19	3	66.4
240502200400230	22	19	4	77.4
240502200500230	22	19	5	88.4
240502200600230	22	19	6	99.4
240502200700230	22	19	7	110.4
240502200800230	22	19	8	121.4
240502600200230	26	26.5	2	74.2
240502600300230	26	26.5	3	89.5
240502600400230	26	26.5	4	104.8
240502600500230	26	26.5	5	120.1
240502600600230	26	26.5	6	135.4
240502600700230	26	26.5	7	150.7
240502600800230	26	26.5	8	166