# Double Swivel Lifting Ring Codipro FE.DSS UP-Female

**Product information**



The FE DSS lifting shackle is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect line up with the lifting sling. The ring can swivel under the load. The ring swivels 180° and has a rotating range of 360°.

**Features:**

- Swiveling under load
- Usable for any kind of lifting operation
- The tightening torque is stamped on all lifting rings in the GRADUP range

... *Read more*


**Material:** High tensile steel
**Marking:** According to standard, CE-mark
**Temperature range:** -20°C up to +200°C
**Standard:** EN 1677-1
*except grade/WLL*

**Safety factor:** 5:1

© November 2026 - All Rights Reserved

# Double Swivel Lifting Ring Codipro FE.DSS UP-Female

## Blueprint



## Technical data

| Part code | WLL ton | Thread | Torque Nm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | L Maxi mm | S mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 4215FEDSSM24UP | 4.5 | M 24 (x3) | 160 | 66 | 31 | 70 | 98 | 73 | 149 | 33 | 66 | 50 | 5.1 |
| 4215FEDSSM27UP | 5.2 | M 27 (x3) | 200 | 66 | 31 | 70 | 98 | 73 | 149 | 33 | 66 | 50 | 5.1 |
| 4215FEDSSM30UP | 7.5 | M 30 (x3.5) | 250 | 66 | 31 | 70 | 98 | 73 | 149 | 33 | 66 | 50 | 5.1 |
| 4215FEDSSM33UP | 8 | M 33 (x3.5) | 250 | 66 | 31 | 70 | 98 | 73 | 149 | 33 | 66 | 50 | 5.1 |
| 4215FEDSSM36UP | 10 | M 36 (x4) | 320 | 66 | 31 | 70 | 98 | 73 | 149 | 33 | 66 | 50 | 5.1 |
| 4215FEDSSM39UP | 12 | M 39 (x4) | 320 | 89 | 38 | 95 | 123 | 91 | 182 | 45 | 89 | 60 | 10 |
| 4215FEDSSM42UP | 13 | M 42 (x4,5) | 400 | 89 | 38 | 95 | 123 | 91 | 182 | 45 | 89 | 60 | 10 |
| 4215FEDSSM45UP | 14.5 | M 45 (x4,5) | 400 | 89 | 38 | 95 | 123 | 91 | 182 | 45 | 89 | 60 | 10 |
| 4215FEDSSM48UP | 17 | M 48 (x5) | 600 | 89 | 38 | 95 | 123 | 91 | 182 | 45 | 89 | 60 | 10 |
| 4215FEDSSM52UP | 19 | M 52 (x5) | 600 | 89 | 38 | 95 | 123 | 91 | 182 | 45 | 89 | 60 | 10 |

© November 2026 - All Rights Reserved