



Wall Mounted Jib Crane OB

Product information

Wall mounted jib cranes comprise an arm and a pair of brackets that can be bolted or welded to an existing wall or building column/stanchion/pillar. A structural engineer must test the support structure to ensure it is strong enough to sustain the weight of the jib crane when loaded.

The arm is located between the clamping brackets and fixed using a pivot pin. The arm rotates around the support column and enables lifting within a predetermined arc.

Features:

- Capacity up to 1000 kg
- Outreach up to 6 m
- Electrical festoon supply: runs inside the arm track

Material: Stainless steel 304/316

Finish: Zinc plated/powder coating

Part code	WLL ton	Length m	Profile No.	Bolt Ø mm	B,	R mm	B2 mm	h1 mm	W1	W2	Delivery time
602524J053	0.08	3	24,000	M20	500	3,000	720	65	500	380	0
602524J064	0.08	4	24,000	M20	600	4,000	820	65	500	380	0
602524J095	0.08	5	24,000	M20	900	5,000	1,120	65	500	380	0
602525J096	0.08	6	25,000	M20	900	6,000	1,120	77	500	380	0
602525J053	0.125	3	25,000	M20	500	3,000	720	77	500	380	0
602525J064	0.125	4	25,000	M20	600	4,000	820	77	500	380	0
602525J095	0.125	5	25,000	M20	900	5,000	1,120	77	500	380	0
602525J106	0.125	6	25,000	M20	1,000	6,000	1,220	77	500	380	0
602525J063	0.25	3	25,000	M20	600	3,000	820	77	500	380	0
602525J084	0.25	4	25,000	M20	800	4,000	1,020	77	500	380	0
602526J095	0.25	5	26,000	M20	900	5,000	1,120	94	500	380	0
602526J106	0.25	6	26,000	M20	1,000	6,000	1,220	94	500	380	0
602526J083	0.5	3	26,000	M20	800	3,000	1,020	94	500	380	0
602526J094	0.5	4	26,000	M20	900	4,000	1,120	94	500	380	0
602527J105	0.5	5	27,000	M20	1,000	5,000	1,220	123	500	380	0
602527J116	0.5	6	27,000	M20	1,100	6,000	1,320	123	500	380	0
602527J093	1	3	27,000	M20	900	3,000	1,120	123	500	380	0
602527J104	1	4	27,000	M20	1,000	4,000	1,220	123	500	380	0

Blueprint

