



Gantry crane, Porta Gantry Rapide 250-1000 kg

Product information

Goods WLL: Up to 1000kg

Personnel WLL: Up to 500kg

3 Person fall arrest: EN795:1997 certified – as part of an EN363 compliant system.

ATEX: Suitable for use in atex zone 2 explosive atmospheres

Lightweight & portable

Easy use:

- Adaptable, multi-purpose trolleys - goods and personnel rated

- Load bearing, lockable castors for easy positioning (acop advises no gantry movement under load except where a competent person has undertaken a suitable risk assessment & method statement and has deemed appropriate)

Configurations: Range of beam lengths up to 4m and configurations available

Availability: 14 Days

Part code	WLL ton	Max. number of persons	Standard Beam Length mm	Max user weight kg	Weight kg	Delivery time
6015PGRT20	0.25	1	2,000	125	45	0
6015PGRS40	0.25	1	4,000	125	46	0
6015PGRT23	0.25	1	2,300	125	46	0
6015PGRT40	0.25	1	4,000	125	51	0
6015PGRS23	0.4	2	2,300	200	41	0
6015PGRM20	0.4	2	2,000	200	41	0
6015PGRM23	0.4	2	2,300	200	42	0
6015PGRM40	0.4	2	4,000	200	47	0
6015PGRS20	0.5	3	2,000	250	40	0

Technical data

Blueprint

