

Gantry Crane, Porta Gantry 500-5000kg

Product information



Lightweight Gantry Crane for lifting of goods and persons. The PORTAGANTRY has the ability to be moved under load. (Subject to detailed instruction and supervision by a competent person).

Goods WLL: 500kg up to 5000kg (depending on model)

Personnel WLL: Maximum combined personnel lifting capacity up to 2500kg (depending on model)

3-5 Person fall arrest: EN795:1997 certified – as part of an EN363 compliant system (500 & 1000 - 3 persons, 2000, 3000 & 5000 - 5 persons)

ATEX: All models suitable for use in ATEX Zone 2 explosive atmospheres

Lightweight & portable: With easy on-site assembly within manual handling guidelines:

- 4 portable parts assembled on just 4 bolts
- Simple 'scissoring' assembly in just 2-3 minutes

Ergonomic

- 360° swivel-locking castors as standard
- Simple, manual height & span adjustment
- Ultra-safe captive trolley
- Ergonomic design of profiles and handles

Stable: Bolted structure, lateral beam and leg bracing features

Configurations: Variety of standard configurations available, plus customisation for specific requirements and interchangeable components (subject to WLL rating)

Availability: 14 Days

... [Read more](#)

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500S2500A	0.5	A-frame S	250	32	3	2,500	1,595	2,345	1.58	89
6015PGAS00500S3000A	0.5	A-frame S	250	32	3	3,000	1,595	2,345	2.08	93
6015PGAS00500S3920A	0.5	A-frame S	250	32	3	3,920	1,595	2,345	3	100
6015PGAS00500S4570A	0.5	A-frame S	250	32	3	4,570	1,595	2,345	3.65	104
6015PGAS00500M2500A	0.5	A-frame M	250	42	3	2,500	2,091	2,841	1.58	109
6015PGAS00500S5500A	0.5	A-frame S	250	32	3	5,500	1,595	2,345	4.58	111
6015PGAS00500M3000A	0.5	A-frame M	250	42	3	3,000	2,091	2,841	2.08	113
6015PGAS00500S6000A	0.5	A-frame S	250	32	3	6,000	1,595	2,345	5.08	115
6015PGAS00500M3920A	0.5	A-frame M	250	42	3	3,920	2,091	2,841	3	120
6015PGAS00500M4570A	0.5	A-frame M	250	42	3	4,570	2,091	2,841	3.65	124
6015PGAS00500I3000A	0.5	A-frame I	250	50	3	3,000	2,178	3,178	2.08	129
6015PGAS00500M5500A	0.5	A-frame M	250	42	3	5,500	2,091	2,841	4.58	131
6015PGAS00500S8400A	0.5	A-frame S	250	32	3	8,400	1,595	2,345	7.48	132
6015PGAS00500M6000A	0.5	A-frame M	250	42	3	6,000	2,091	2,841	5.08	135
6015PGAS00500I3920A	0.5	A-frame I	250	50	3	3,920	2,178	3,178	3	136
6015PGAS00500S9000A	0.5	A-frame S	250	32	3	9,000	1,595	2,345	8.08	137
6015PGAS00500I4570A	0.5	A-frame I	250	50	3	4,570	2,178	3,178	3.65	141
6015PGAS00500T3000A	0.5	A-frame T	250	56	3	3,000	2,869	4,069	2.08	141
6015PGAS00500I5500A	0.5	A-frame I	250	50	3	5,500	2,178	3,178	4.58	148
6015PGAS00500T3920A	0.5	A-frame T	250	56	3	3,920	2,869	4,069	3	148
6015PGAS00500I6000A	0.5	A-frame I	250	50	3	6,000	2,178	3,178	5.08	151
6015PGAS00500M8400A	0.5	A-frame M	250	42	3	8,400	2,091	2,841	7.48	152
6015PGAS00500T4570A	0.5	A-frame T	250	56	3	4,570	2,869	4,069	3.65	153
6015PGAS00500M9000A	0.5	A-frame M	250	42	3	9,000	2,091	2,841	8.08	157
6015PGAS00500T5500A	0.5	A-frame T	250	56	3	5,500	2,869	4,069	4.58	159
6015PGAS00500T6000A	0.5	A-frame T	250	56	3	6,000	2,869	4,069	5.08	163
6015PGAS00500I8400A	0.5	A-frame I	250	50	3	8,400	2,178	3,178	7.48	169
6015PGAS00500I9000A	0.5	A-frame I	250	50	3	9,000	2,178	3,178	8.08	173
6015PGAS00500T8400A	0.5	A-frame T	250	56	3	8,400	2,869	4,069	7.48	180
6015PGAS00500T9000A	0.5	A-frame T	250	56	3	9,000	2,869	4,069	8.08	185
6015PGAS00500TC43920A	0.5	A-frame TC4	250	86	3	3,920	3,317	4,517	3	208

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500TC44570A	0.5	A-frame TC4	250	86	3	4,570	3,317	4,517	3.65	212
6015PGAS00500TC33920A	0.5	A-frame TC3	250	91	3	3,920	3,817	5,017	3	218
6015PGAS00500TC45500A	0.5	A-frame TC4	250	86	3	5,500	3,317	4,517	4.58	219
6015PGAS00500TC34570A	0.5	A-frame TC3	250	91	3	4,570	3,817	5,017	3.65	222
6015PGAS00500TC46000A	0.5	A-frame TC4	250	86	3	6,000	3,317	4,517	5.08	223
6015PGAS00500TC35500A	0.5	A-frame TC3	250	91	3	5,500	3,817	5,017	4.58	229
6015PGAS00500TC23920A	0.5	A-frame TC2	250	97	3	3,920	3,917	5,517	3	230
6015PGAS00500TC36000A	0.5	A-frame TC3	250	91	3	6,000	3,817	5,017	5.08	233
6015PGAS00500TC24570A	0.5	A-frame TC2	250	97	3	4,570	3,917	5,517	3.65	234
6015PGAS00500TC48400A	0.5	A-frame TC4	250	86	3	8,400	3,317	4,517	7.48	240
6015PGAS00500TC13920A	0.5	A-frame TC1	250	102	3	3,920	4,019	5,819	3	240
6015PGAS00500TC25500A	0.5	A-frame TC2	250	97	3	5,500	3,917	5,517	4.58	241
6015PGAS00500TC49000A	0.5	A-frame TC4	250	86	3	9,000	3,317	4,517	8.08	245
6015PGAS00500TC26000A	0.5	A-frame TC2	250	97	3	6,000	3,917	5,517	5.08	245
6015PGAS00500TC14570A	0.5	A-frame TC1	250	102	3	4,570	4,019	5,819	3.65	245
6015PGAS00500TC38400A	0.5	A-frame TC3	250	91	3	8,400	3,817	5,017	7.48	250
6015PGAS00500TC15500A	0.5	A-frame TC1	250	102	3	5,500	4,019	5,819	4.58	252
6015PGAS00500TC39000A	0.5	A-frame TC3	250	91	3	9,000	3,817	5,017	8.08	255
6015PGAS00500TC16000A	0.5	A-frame TC1	250	102	3	6,000	4,019	5,819	5.08	255
6015PGAS00500TC28400A	0.5	A-frame TC2	250	97	3	8,400	3,917	5,517	7.48	263
6015PGAS00500TC29000A	0.5	A-frame TC2	250	97	3	9,000	3,917	5,517	8.08	267
6015PGAS00500TC18400A	0.5	A-frame TC1	250	102	3	8,400	4,019	5,819	7.48	273
6015PGAS00500TC19000A	0.5	A-frame TC1	250	102	3	9,000	4,019	5,819	8.08	277
6015PGAS00500I2500A	0.5	A-frame I	250	50	3	2,500	2,178	3,178	1.58	-
6015PGAS00500T2500A	0.5	A-frame T	250	56	3	2,500	2,869	4,069	1.58	-
6015PGAS00500TC42500A	0.5	A-frame TC4	250	86	3	2,500	3,317	4,517	1.58	-
6015PGAS00500TC43000A	0.5	A-frame TC4	250	86	3	3,000	3,317	4,517	2.08	-
6015PGAS00500TC32500A	0.5	A-frame TC3	250	91	3	2,500	3,817	5,017	1.58	-
6015PGAS00500TC33000A	0.5	A-frame TC3	250	91	3	3,000	3,817	5,017	2.08	-
6015PGAS00500TC22500A	0.5	A-frame TC2	250	97	3	2,500	3,917	5,517	1.58	-

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS00500TC23000A	0.5	A-frame TC2	250	97	3	3,000	3,917	5,517	2.08	-
6015PGAS00500TC12500A	0.5	A-frame TC1	250	102	3	2,500	4,019	5,819	1.58	-
6015PGAS00500TC13000A	0.5	A-frame TC1	250	102	3	3,000	4,019	5,819	2.08	-
6015PGAS01000S2500A	1	A-frame S	500	32	3	2,500	1,605	2,355	1.58	89
6015PGAS01000S3000A	1	A-frame S	500	32	3	3,000	1,605	2,355	2.08	93
6015PGAS01000S3920A	1	A-frame S	500	32	3	3,920	1,605	2,355	3	100
6015PGAS01000S4570A	1	A-frame S	500	32	3	4,570	1,605	2,355	3.65	104
6015PGAS01000M2500A	1	A-frame M	500	42	3	2,500	2,101	2,851	1.58	109
6015PGAS01000S5500A	1	A-frame S	500	32	3	5,500	1,605	2,355	4.58	111
6015PGAS01000M3000A	1	A-frame M	500	42	3	3,000	2,101	2,851	2.08	113
6015PGAS01000S6000A	1	A-frame S	500	32	3	6,000	1,605	2,355	5.08	115
6015PGAS01000M3920A	1	A-frame M	500	42	3	3,920	2,101	2,851	3	120
6015PGAS01000M4570A	1	A-frame M	500	42	3	4,570	2,101	2,851	3.65	124
6015PGAS01000I3000A	1	A-frame I	500	50	3	3,000	2,188	3,188	2.08	129
6015PGAS01000M5500A	1	A-frame M	500	42	3	5,500	2,101	2,851	4.58	131
6015PGAS01000M6000A	1	A-frame M	500	42	3	6,000	2,101	2,851	5.08	135
6015PGAS01000I3920A	1	A-frame I	500	50	3	3,920	2,188	3,188	3	136
6015PGAS01000I4570A	1	A-frame I	500	50	3	4,570	2,188	3,188	3.65	141
6015PGAS01000T3000A	1	A-frame T	500	56	3	3,000	2,879	4,079	2.08	141
6015PGAS01000I5500A	1	A-frame I	500	50	3	5,500	2,188	3,188	4.58	148
6015PGAS01000T3920A	1	A-frame T	500	56	3	3,920	2,879	4,079	3	148
6015PGAS01000S8400A	1	A-frame S	500	32	3	8,400	1,605	2,355	7.48	149
6015PGAS01000I6000A	1	A-frame I	500	50	3	6,000	2,188	3,188	5.08	151
6015PGAS01000T4570A	1	A-frame T	500	56	3	4,570	2,879	4,079	3.65	152
6015PGAS01000S9000A	1	A-frame S	500	32	3	9,000	1,605	2,355	8.08	155
6015PGAS01000T5500A	1	A-frame T	500	56	3	5,500	2,879	4,079	4.58	159
6015PGAS01000T6000A	1	A-frame T	500	56	3	6,000	2,879	4,079	5.08	163
6015PGAS01000M8400A	1	A-frame M	500	42	3	8,400	2,101	2,851	7.48	169
6015PGAS01000M9000A	1	A-frame M	500	42	3	9,000	2,101	2,851	8.08	175
6015PGAS01000I8400A	1	A-frame I	500	50	3	8,400	2,188	3,188	7.48	186
6015PGAS01000I9000A	1	A-frame I	500	50	3	9,000	2,188	3,188	8.08	191

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS01000T8400A	1	A-frame T	500	56	3	8,400	2,879	4,079	7.48	197
6015PGAS01000T9000A	1	A-frame T	500	56	3	9,000	2,879	4,079	8.08	203
6015PGAS01000TC43920A	1	A-frame TC4	500	86	3	3,920	3,327	4,527	3	208
6015PGAS01000TC44570A	1	A-frame TC4	500	86	3	4,570	3,327	4,527	3.65	212
6015PGAS01000TC33920A	1	A-frame TC3	500	91	3	3,920	3,827	5,027	3	218
6015PGAS01000TC45500A	1	A-frame TC4	500	86	3	5,500	3,327	4,527	4.58	219
6015PGAS01000TC34570A	1	A-frame TC3	500	91	3	4,570	3,827	5,027	3.65	222
6015PGAS01000TC46000A	1	A-frame TC4	500	86	3	6,000	3,327	4,527	5.08	223
6015PGAS01000TC35500A	1	A-frame TC3	500	91	3	5,500	3,827	5,027	4.58	229
6015PGAS01000TC23920A	1	A-frame TC2	500	97	3	3,920	3,927	5,527	3	230
6015PGAS01000TC36000A	1	A-frame TC3	500	91	3	6,000	3,827	5,027	5.08	233
6015PGAS01000TC24570A	1	A-frame TC2	500	97	3	4,570	3,927	5,527	3.65	234
6015PGAS01000TC13920A	1	A-frame TC1	500	102	3	3,920	4,029	5,829	3	240
6015PGAS01000TC25500A	1	A-frame TC2	500	97	3	5,500	3,927	5,527	4.58	241
6015PGAS01000TC26000A	1	A-frame TC2	500	97	3	6,000	3,927	5,527	5.08	245
6015PGAS01000TC14570A	1	A-frame TC1	500	102	3	4,570	4,029	5,829	3.65	245
6015PGAS01000TC15500A	1	A-frame TC1	500	102	3	5,500	4,029	5,829	4.58	252
6015PGAS01000TC16000A	1	A-frame TC1	500	102	3	6,000	4,029	5,829	5.08	255
6015PGAS01000TC48400A	1	A-frame TC4	500	86	3	8,400	3,327	4,527	7.48	257
6015PGAS01000TC49000A	1	A-frame TC4	500	86	3	9,000	3,327	4,527	8.08	263
6015PGAS01000TC38400A	1	A-frame TC3	500	91	3	8,400	3,827	5,027	7.48	267
6015PGAS01000TC39000A	1	A-frame TC3	500	91	3	9,000	3,827	5,027	8.08	273
6015PGAS01000TC28400A	1	A-frame TC2	500	97	3	8,400	3,927	5,527	7.48	279
6015PGAS01000TC29000A	1	A-frame TC2	500	97	3	9,000	3,927	5,527	8.08	285
6015PGAS01000TC18400A	1	A-frame TC1	500	102	3	8,400	4,029	5,829	7.48	289
6015PGAS01000TC19000A	1	A-frame TC1	500	102	3	9,000	4,029	5,829	8.08	295
6015PGAS01000I2500A	1	A-frame I	500	50	3	2,500	2,188	3,188	1.58	-
6015PGAS01000T2500A	1	A-frame T	500	56	3	2,500	2,879	4,079	1.58	-
6015PGAS01000TC42500A	1	A-frame TC4	500	86	3	2,500	3,327	4,527	1.58	-
6015PGAS01000TC43000A	1	A-frame TC4	500	86	3	3,000	3,327	4,527	2.08	-
6015PGAS01000TC32500A	1	A-frame TC3	500	91	3	2,500	3,827	5,027	1.58	-

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS01000TC33000A	1	A-frame TC3	500	91	3	3,000	3,827	5,027	2.08	-
6015PGAS01000TC22500A	1	A-frame TC2	500	97	3	2,500	3,927	5,527	1.58	-
6015PGAS01000TC23000A	1	A-frame TC2	500	97	3	3,000	3,927	5,527	2.08	-
6015PGAS01000TC12500A	1	A-frame TC1	500	102	3	2,500	4,029	5,829	1.58	-
6015PGAS01000TC13000A	1	A-frame TC1	500	102	3	3,000	4,029	5,829	2.08	-
6015PGAS02000S2500A	2	A-frame S	1,000	35	5	2,500	1,605	2,355	1.58	95
6015PGAS02000S3000A	2	A-frame S	1,000	35	5	3,000	1,605	2,355	2.08	99
6015PGAS02000S3920A	2	A-frame S	1,000	35	5	3,920	1,605	2,355	3	106
6015PGAS02000M2500A	2	A-frame M	1,000	42	5	2,500	1,605	2,851	1.58	109
6015PGAS02000S4570A	2	A-frame S	1,000	35	5	4,570	1,605	2,355	3.65	110
6015PGAS02000M3000A	2	A-frame M	1,000	42	5	3,000	2,101	2,851	2.08	113
6015PGAS02000M3920A	2	A-frame M	1,000	42	5	3,920	2,101	2,851	3	120
6015PGAS02000M4570A	2	A-frame M	1,000	42	5	4,570	2,101	2,851	3.65	124
6015PGAS02000S5500A	2	A-frame S	1,000	35	5	5,500	1,605	2,355	4.58	128
6015PGAS02000I3000A	2	A-frame I	1,000	50	5	3,000	2,188	3,188	2.08	129
6015PGAS02000I3920A	2	A-frame I	1,000	50	5	3,920	2,188	3,188	3	136
6015PGAS02000I4570A	2	A-frame I	1,000	50	5	4,570	2,188	3,188	3.65	141
6015PGAS02000T3000A	2	A-frame T	1,000	56	5	3,000	2,879	4,079	2.08	141
6015PGAS02000M5500A	2	A-frame M	1,000	42	5	5,500	2,101	2,851	4.58	142
6015PGAS02000T3920A	2	A-frame T	1,000	56	5	3,920	2,879	4,079	3	148
6015PGAS02000T4570A	2	A-frame T	1,000	56	5	4,570	2,879	4,079	3.65	152
6015PGAS02000I5500A	2	A-frame I	1,000	50	5	5,500	2,188	3,188	4.58	159
6015PGAS02000T5500A	2	A-frame T	1,000	56	5	5,500	2,879	4,079	4.58	170
6015PGAS02000S6000A	2	A-frame S	1,000	35	5	6,000	1,605	2,355	5.08	174
6015PGAS02000M6000A	2	A-frame M	1,000	42	5	6,000	2,101	2,851	5.08	188
6015PGAS02000I6000A	2	A-frame I	1,000	50	5	6,000	2,188	3,188	5.08	204
6015PGAS02000TC43920A	2	A-frame TC4	1,000	86	5	3,920	3,327	4,527	3	208
6015PGAS02000S8400A	2	A-frame S	1,000	35	5	8,400	1,605	2,355	7.48	211
6015PGAS02000TC44570A	2	A-frame TC4	1,000	86	5	4,570	3,327	4,527	3.65	212
6015PGAS02000T6000A	2	A-frame T	1,000	56	5	6,000	2,879	4,079	5.08	215
6015PGAS02000TC33920A	2	A-frame TC3	1,000	91	5	3,920	3,827	5,027	3	218

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS02000TC34570A	2	A-frame TC3	1,000	91	5	4,570	3,827	5,027	3.65	222
6015PGAS02000M8400A	2	A-frame M	1,000	42	5	8,400	2,101	2,851	7.48	225
6015PGAS02000TC45500A	2	A-frame TC4	1,000	86	5	5,500	3,327	4,527	4.58	230
6015PGAS02000TC23920A	2	A-frame TC2	1,000	97	5	3,920	3,927	5,527	3	230
6015PGAS02000TC24570A	2	A-frame TC2	1,000	97	5	4,570	3,927	5,527	3.65	235
6015PGAS02000TC35500A	2	A-frame TC3	1,000	91	5	5,500	3,827	5,027	4.58	240
6015PGAS02000TC13920A	2	A-frame TC1	1,000	102	5	3,920	4,029	5,829	3	240
6015PGAS02000I8400A	2	A-frame I	1,000	50	5	8,400	2,188	3,188	7.48	242
6015PGAS02000TC14570A	2	A-frame TC1	1,000	102	5	4,570	4,029	5,829	3.65	244
6015PGAS02000TC25500A	2	A-frame TC2	1,000	97	5	5,500	3,927	5,527	4.58	252
6015PGAS02000T8400A	2	A-frame T	1,000	56	5	8,400	2,879	4,079	7.48	253
6015PGAS02000TC15500A	2	A-frame TC1	1,000	102	5	5,500	4,029	5,829	4.58	262
6015PGAS02000TC46000A	2	A-frame TC4	1,000	86	5	6,000	3,327	4,527	5.08	276
6015PGAS02000TC36000A	2	A-frame TC3	1,000	91	5	6,000	3,827	5,027	5.08	286
6015PGAS02000TC26000A	2	A-frame TC2	1,000	97	5	6,000	3,927	5,527	5.08	298
6015PGAS02000TC16000A	2	A-frame TC1	1,000	102	5	6,000	4,029	5,829	5.08	308
6015PGAS02000TC48400A	2	A-frame TC4	1,000	86	5	8,400	3,327	4,527	7.48	313
6015PGAS02000TC38400A	2	A-frame TC3	1,000	91	5	8,400	3,827	5,027	7.48	323
6015PGAS02000TC28400A	2	A-frame TC2	1,000	97	5	8,400	3,927	5,527	7.48	335
6015PGAS02000TC18400A	2	A-frame TC1	1,000	102	5	8,400	4,029	5,829	7.48	345
6015PGAS02000I2500A	2	A-frame I	1,000	50	5	2,500	2,188	3,188	1.58	-
6015PGAS02000T2500A	2	A-frame T	1,000	56	5	2,500	2,879	4,079	1.58	-
6015PGAS02000TC42500A	2	A-frame TC4	1,000	86	5	2,500	3,327	4,527	1.58	-
6015PGAS02000TC43000A	2	A-frame TC4	1,000	86	5	3,000	3,327	4,527	2.08	-
6015PGAS02000TC32500A	2	A-frame TC3	1,000	91	5	2,500	3,827	5,027	1.58	-
6015PGAS02000TC33000A	2	A-frame TC3	1,000	91	5	3,000	3,827	5,027	2.08	-
6015PGAS02000TC22500A	2	A-frame TC2	1,000	97	5	2,500	3,927	5,527	1.58	-
6015PGAS02000TC23000A	2	A-frame TC2	1,000	97	5	3,000	3,927	5,527	2.08	-
6015PGAS02000TC12500A	2	A-frame TC1	1,000	102	5	2,500	4,029	5,829	1.58	-
6015PGAS02000TC13000A	2	A-frame TC1	1,000	102	5	3,000	4,029	5,829	2.08	-
6015PGAS03000S2500A	3	A-frame S	1,500	56	5	2,500	1,605	2,410	1.58	137

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS03000S3000A	3	A-frame S	1,500	56	5	3,000	1,605	2,410	2.08	141
6015PGAS03000M2500A	3	A-frame M	1,500	61	5	2,500	1,605	2,906	1.58	147
6015PGAS03000M3000A	3	A-frame M	1,500	61	5	3,000	2,101	2,906	2.08	151
6015PGAS03000S3920A	3	A-frame S	1,500	56	5	3,920	1,605	2,410	3	156
6015PGAS03000S4570A	3	A-frame S	1,500	56	5	4,570	1,605	2,410	3.65	162
6015PGAS03000M3920A	3	A-frame M	1,500	61	5	3,920	2,101	2,906	3	166
6015PGAS03000M4570A	3	A-frame M	1,500	61	5	4,570	2,101	2,906	3.65	172
6015PGAS03000I3000A	3	A-frame I	1,500	73	5	3,000	2,188	3,188	2.08	175
6015PGAS03000I3920A	3	A-frame I	1,500	73	5	3,920	2,188	3,188	3	190
6015PGAS03000I4570A	3	A-frame I	1,500	73	5	4,570	2,188	3,188	3.65	196
6015PGAS03000T3000A	3	A-frame T	1,500	85	5	3,000	2,879	4,079	2.08	199
6015PGAS03000S5500A	3	A-frame S	1,500	56	5	5,500	1,605	2,410	4.58	208
6015PGAS03000T3920A	3	A-frame T	1,500	85	5	3,920	2,879	4,079	3	214
6015PGAS03000S6000A	3	A-frame S	1,500	56	5	6,000	1,605	2,410	5.08	216
6015PGAS03000TC43920A	3	A-frame TC4	1,500	86	5	3,920	3,327	4,527	3	216
6015PGAS03000M5500A	3	A-frame M	1,500	61	5	5,500	2,101	2,906	4.58	218
6015PGAS03000T4570A	3	A-frame T	1,500	85	5	4,570	2,879	4,079	3.65	220
6015PGAS03000TC44570A	3	A-frame TC4	1,500	86	5	4,570	3,327	4,527	3.65	222
6015PGAS03000M6000A	3	A-frame M	1,500	61	5	6,000	2,101	2,906	5.08	226
6015PGAS03000TC33920A	3	A-frame TC3	1,500	91	5	3,920	3,827	5,027	3	226
6015PGAS03000TC34570A	3	A-frame TC3	1,500	91	5	4,570	3,827	5,027	3.65	232
6015PGAS03000TC23920A	3	A-frame TC2	1,500	97	5	3,920	3,927	5,527	3	238
6015PGAS03000I5500A	3	A-frame I	1,500	73	5	5,500	2,188	3,188	4.58	242
6015PGAS03000TC24570A	3	A-frame TC2	1,500	97	5	4,570	3,927	5,527	3.65	244
6015PGAS03000I6000A	3	A-frame I	1,500	73	5	6,000	2,188	3,188	5.08	250
6015PGAS03000S8400A	3	A-frame S	1,500	56	5	8,400	1,605	2,410	7.48	253
6015PGAS03000M8400A	3	A-frame M	1,500	61	5	8,400	2,101	2,906	7.48	263
6015PGAS03000T5500A	3	A-frame T	1,500	85	5	5,500	2,879	4,079	4.58	266
6015PGAS03000TC45500A	3	A-frame TC4	1,500	86	5	5,500	3,327	4,527	4.58	268
6015PGAS03000T6000A	3	A-frame T	1,500	85	5	6,000	2,879	4,079	5.08	274
6015PGAS03000TC46000A	3	A-frame TC4	1,500	86	5	6,000	3,327	4,527	5.08	276

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS03000TC35500A	3	A-frame TC3	1,500	91	5	5,500	3,827	5,027	4.58	278
6015PGAS03000TC36000A	3	A-frame TC3	1,500	91	5	6,000	3,827	5,027	5.08	286
6015PGAS03000I8400A	3	A-frame I	1,500	73	5	8,400	2,188	3,188	7.48	287
6015PGAS03000TC25500A	3	A-frame TC2	1,500	97	5	5,500	3,927	5,527	4.58	290
6015PGAS03000TC26000A	3	A-frame TC2	1,500	97	5	6,000	3,927	5,527	5.08	298
6015PGAS03000T8400A	3	A-frame T	1,500	85	5	8,400	2,879	4,079	7.48	311
6015PGAS03000TC48400A	3	A-frame TC4	1,500	86	5	8,400	3,327	4,527	7.48	313
6015PGAS03000TC38400A	3	A-frame TC3	1,500	91	5	8,400	3,827	5,027	7.48	323
6015PGAS03000TC28400A	3	A-frame TC2	1,500	99	5	8,400	3,927	5,527	7.48	335
6015PGAS03000I2500A	3	A-frame I	1,500	73	5	2,500	2,188	3,188	1.58	-
6015PGAS03000T2500A	3	A-frame T	1,500	85	5	2,500	2,879	4,079	1.58	-
6015PGAS03000TC42500A	3	A-frame TC4	1,500	86	5	2,500	3,327	4,527	1.58	-
6015PGAS03000TC43000A	3	A-frame TC4	1,500	86	5	3,000	3,327	4,527	2.08	-
6015PGAS03000TC32500A	3	A-frame TC3	1,500	91	5	2,500	3,827	5,027	1.58	-
6015PGAS03000TC33000A	3	A-frame TC3	1,500	91	5	3,000	3,827	5,027	2.08	-
6015PGAS03000TC22500A	3	A-frame TC2	1,500	97	5	2,500	3,927	5,527	1.58	-
6015PGAS03000TC23000A	3	A-frame TC2	1,500	97	5	3,000	3,927	5,527	2.08	-
6015PGAS05000IR3000A	5	A-Frame IR	2,500	99	5	3,000	2,181	3,181	2.08	255
6015PGAS05000TC4R3920A	5	A-Frame TC4R	2,500	96	5	3,920	3,300	4,500	3	263
6015PGAS05000IR3920A	5	A-Frame IR	2,500	99	5	3,920	2,181	3,181	3	269
6015PGAS05000TC3R3920A	5	A-Frame TC3R	2,500	101	5	3,920	3,800	5,000	3	273
6015PGAS05000TC4R4570A	5	A-Frame TC4R	2,500	96	5	4,570	3,300	4,500	3.65	274
6015PGAS05000TR3000A	5	A-Frame TR	2,500	109	5	3,000	2,849	4,049	2.08	275
6015PGAS05000IR4570A	5	A-Frame IR	2,500	99	5	4,570	2,181	3,181	3.65	280
6015PGAS05000TC3R4570A	5	A-Frame TC3R	2,500	101	5	4,570	3,800	5,000	3.65	284
6015PGAS05000TC4R5500A	5	A-Frame TC4R	2,500	96	5	5,500	3,300	4,500	4.58	288
6015PGAS05000TR3920A	5	A-Frame TR	2,500	109	5	3,920	2,849	4,049	3	289
6015PGAS05000IR5500A	5	A-Frame IR	2,500	99	5	5,500	2,181	3,181	4.58	294

Gantry Crane, Porta Gantry 500-5000kg

Technical data

Part code	WLL ton	Model	Max load kg	A-Frame weight	Max. number of persons	Standard Beam Length mm	Min height mm	Max height mm	overall span m	Weight kg
6015PGAS05000TC3R5500A	5	A-Frame TC3R	2,500	101	5	5,500	3,800	5,000	4.58	298
6015PGAS05000TR4570A	5	A-Frame TR	2,500	109	5	4,570	2,849	4,049	3.65	300
6015PGAS05000TR5500A	5	A-Frame TR	2,500	109	5	5,500	2,849	4,049	4.58	314
6015PGAS05000IR2500A	5	A-Frame IR	2,500	99	5	2,500	2,181	3,181	1.58	-
6015PGAS05000TR2500A	5	A-Frame TR	2,500	109	5	2,500	2,849	4,049	1.58	-
6015PGAS05000TC4R2500A	5	A-Frame TC4R	2,500	96	5	2,500	3,300	4,500	1.58	-
6015PGAS05000TC4R3000A	5	A-Frame TC4R	2,500	96	5	3,000	3,300	4,500	2.08	-
6015PGAS05000TC3R2500A	5	A-Frame TC3R	2,500	96	5	2,500	3,800	5,000	1.58	-
6015PGAS05000TC3R3000A	5	A-Frame TC3R	2,500	101	5	3,000	3,800	5,000	2.08	-