Coupling Link, Gunnebo G Classic

Product information



For use with master link and eye hook.

... *Read more*


Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated.

Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Coupling Link, Gunnebo G Classic

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	F mm	L mm	Weight kg
401200110110	G-6-8	6	1.1	8	15	17	7	45	0.1
401200200110	G-7/8-8	7-8	2	11	18	22	9	56	0.2
401200320110	G-10-8	10	3.2	13	25	26	11	68	0.3
401200540110	G-13-8	13	5.4	16	30	33	15	89	0.7
401200820110	G-16-8	16	8.2	20	36	40	19	105	1.2
401201280110	G-18/20-8	19	12.8	23	43	47	22	125	1.9
401201550110	G-22-8	22	15.5	26	50	59	24	152	3
401202170110	G-26-8	26	21.7	33	58	61	30	161	5.2
401203280110	G-32-8	32	32.8	40	70	77	38	200	9.5

© November 2026 - All Rights Reserved