Roller-bearing Swivel Gunnebo SKLI/SKLU Classic

Product information



Electrically insulated, lubricated, sealed roller bearing swivel. Fully rotational even at maximum load. Tested to resist 1000 V. Suitable for protection of overhead cranes during welding operations on suspended loads.

... *Read more*


Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Standard: EN 1677
Warning: Not to be heat treated.

Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Roller-bearing Swivel Gunnebo SKLI/SKLU Classic

Blueprint



Technical data

Part code	Code	WLL ton	For chain Ø mm	D mm	L mm	Weight kg
422500200160	SKLI-7/8-8	2	7, 8	48	75	0.7
422500320160	SKLI-10-8	3.2	10	59	97	1.3
422500540160	SKLI-13-8	5.4	13	75	120	2.8
422500800160	SKLI-16-8	8	16	90	137	4.6
422501280160	SKLI-18/20-8	12.8	19	104	159	7.3
422501550160	SKLU-22-8*	15.5	22	109	160	9.2
422502170160	SKLU-26-8*	21.7	26	135	207	18.3

© November 2026 - All Rights Reserved