ROV Retrieve Shackle no 861, Gunnebo

Product information

The ROV Retrieve Shackle is designed for smooth and easy use in retrieving and releasing subsea lifting and rigging operations.

... *Read more*




Material: High tensile steel, quenched and tempered
Marking: According to standard, CE-mark
Temperature range: -40°C up to 200°C
Finish: All load bearing parts hot dip galvanized
Standard: EN 13889

Safety factor: 6:1

© November 2026 - All Rights Reserved

ROV Retrieve Shackle no 861, Gunnebo

Blueprint



Technical data

Part code	WLL ton	A mm	C mm	d mm	d1 mm	E mm	F mm	G mm	H mm	I mm	L mm	Weight kg
420100950350	9.5	46	108	28	32	74	60	33	132	31	440	6.5
420101200350	12	52	119	32	35	83	60	33	132	31	460	8
420101700350	17	60	146	38	42	98	63.5	33	132	31	501	10
420102500350	25	74	178	45	50	127	70	33	132	31	565	15.7
420103500350	35	83	197	50	57	138	76	33	132	31	604	20
420105500350	55	105	260	65	70	180	88	33	132	31	712	42
420108500350	85	133	330	84	83	190	108	33	132	31	745	78.3

© November 2026 - All Rights Reserved