

Master Link MF GrabiQ V2

Product information



Designed for use with chain, wire or synthetic rope. For 1-leg, 2-leg, 3/4-leg slings ... [Read more](#)

Material: Alloy Steel

Marking: According to standard, Code, grade, chain size, manufacturing ID


Standard: EN 1677-4 (+25% WLL) , AS 3775, AS 3776

Safety factor: 5:1

Grade: 10

Master Link MF GrabiQ V2

Blueprint



Technical data

| Part code | Code | WLL ton | L mm | E mm | D, mm | Weight kg |
|--------------|----------------------|---------|------|------|-------|-----------|
| 402100201180 | MF-6-10 GrabiQ V2 | 2 | 100 | 60 | 11 | 0.2 |
| 402100321180 | MF-86-10 GrabiQ V2 | 3.2 | 120 | 60 | 13 | 0.4 |
| 402100541180 | MF-108-10 GrabiQ V2 | 5.4 | 140 | 80 | 17 | 0.8 |
| 402100821180 | MF-1310-10 GrabiQ V2 | 8.2 | 180 | 95 | 22 | 1.5 |
| 402101361180 | MF-1613-10 GrabiQ V2 | 13.6 | 275 | 145 | 28 | 3.9 |
| 402102061180 | MF-2016-10 GrabiQ V2 | 20.6 | 275 | 145 | 32 | 5.1 |
| 402103201180 | MF-2220-10 GrabiQ V2 | 32 | 270 | 140 | 40 | 8.1 |