



Turnbuckle Jaw-Jaw HD

Product information

The Turnbuckles from De Haan Special Equipment can be used for tightening and lashing operations on land and at sea. Think of lashing shiploads or adjusting construction parts. Turnbuckles cannot be used for lifting purposes. You can choose between a bled or a jaw connection. The connections of the Turnbuckles are geared to steel wire rope sockets and with the standard bow shackles and D-shackles.

Material: High Tensile Steel

Marking: According to standard

Temperature range: -20°C up to +180°C

Finish: Painted RAL 5013 Blue

Standard: EN 10204

Safety factor: 5:1

Part code	WLL ton	B1 mm	B3 mm	Ø D1 mm	L in	L out	R1 mm	T mm
422101350630	13.5	55	20	51	935	1,260	60	120
422101700630	17	65	28	63	1,010	1,360	70	130
422102500630	25	76	30	70	1,085	1,415	70	145
422103000630	30	80	35	72	1,160	1,530	75	160
422103500630	35	90	40	80	1,250	1,650	85	175
422104500630	45	100	45	90	1,300	1,780	95	175
422105500630	55	110	50	100	1,380	1,890	105	175
422107000630	70	110	55	108	1,480	2,025	115	175
422108500630	85	130	75	127	1,565	2,200	135	175
422110000630	100	140	90	140	1,630	2,360	145	175
422112000630	120	155	90	152	1,745	2,340	170	190
422116000630	160	170	100	178	1,870	2,470	190	210
422120000630	200	190	110	190	2,020	2,640	220	250
422125000630	250	210	120	250	2,170	2,840	260	280

Blueprint

