

Lever Hoist YaleERGO 360 UT with safety gear

Product information



Lever hoist YaleERGO 360 UT is optimized for overhead line construction. Its automatic safety gear increases safety in use. The ergonomic design and the integrated handle allow efficient working in any angle, for lifting and pulling applications.

- Automatic safety gear
- Corrosion protection
- Handle integrated to the lever
- Easy maintenance & inspection

Options :

- Chain stopper
- Load limiter (overload protection)

[... Read more](#)


Marking: According to standard

Standard: EN 1808

Safety factor: 4:1

Lever Hoist YaleERGO 360 UT with safety gear

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	Model	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	J mm	K mm	L mm	Mmm mm	Nmm mm	Omm mm	Pmm mm	Weight kg
500500150150490	1.5	1.5	1	YaleERGO 360 UT 1500	375	26	31	21	327	300	51	96	147	69	124	193	30	120	287	9.8
500500300150490	3	1.5	1	YaleERGO 360 UT 3000	445	37	40	28	377	350	57	123	180	86	136	222	30	120	314	18.1
500500600150490	6	1.5	2	YaleERGO 360 UT 6000	563	45	47	35	377	350	71	162	233	86	136	222	30	120	314	29.8
500500900150490	9	1.5	3	YaleERGO 360 UT 9000	695	68	68	50	377	350	116	199	315	86	136	222	30	120	314	50.4