



## Open Spelter Socket with Pin

### Product information

The open spelter socket from the standard series has a wide range of applications as a steel wire rope socket for general use in any situation and under various conditions. If the minimum breaking load of the wire is not higher than that of the open spelter socket, a 100% breaking load of the socket-wire combination is guaranteed. All open spelter sockets come with a pin or bolt. Non-standard sizes or custom products available on request. ISO 3189.

**Working Load Limit:** 20% of the MBL

**Standard certification:** Certificate of Conformity, 3.1 material Certificate EN 10204

**Material:** Cast steel.

**Temperature range:** -40°C up to +200°C

**Finish:** Painted RAL 5013 blue or galvanized.

Part code	Code	Diameter mm	Rope Ø range mm	MBL	Finish	Rope Ø inch	A,	B,	C,	J,	K,	Weight kg
122100700322	192	17.5	6-7	8	Galvanized	1/4	52	39,5	33,5	17,5	8	0.4
122101000322	194	20.5	8-10	12	Galvanized	5/16 - 3/8	58	44,5	39,5	20,5	11	0.8
122101300322	196	25.5	11-13	20	Galvanized	7/16 - 1/2	63,5	51	49	25,5	12	1.3
122101600322	198	30	14-16	30	Galvanized	9/16 - 5/8	76,5	63,5	62	32	14	2.3
122101900322	100	35	17-19	40	Galvanized	3/4	89	76	100	38	16	3.2
122101900320	100	35	17-19	40	Painted	3/4	89	76	100	38	16	3.2
122102200322	104	41	20-22	60	Galvanized	7/8	101	89	85,5	44	19	5

122102200325	104	41	20-22	60	Painted	7/8	101	89	85,5	44	19	5
122102600322	108	51	23-26	75	Galvanized	1	114	101	114	51	22	8.8
122102600325	108	51	23-26	75	Painted	1	114	101	114	51	22	8.8
122103000322	111	57	27-30	100	Galvanized	1 1/8	127	114	123,5	57	25	11.6
122103000325	111	57	27-30	100	Painted	1 1/8	127	114	123,5	57	25	11.6
122103600322	115	63	31-36	125	Galvanized	1 1/4 - 1 3/8	139	127	135	63	28	16.3
122103600325	115	63	31-36	125	Painted	1 1/4 - 1 3/8	139	127	135	63	28	16.3
122103900322	118	70	37-39	150	Galvanized	1 1/2	152	162	152	76	30	23.5
122103900325	118	70	37-39	150	Painted	1 1/2	152	162	152	76	30	23.5
122104200322	120	76	40-42	180	Galvanized	1 5/8	165	165	168	76	33	29
122104200325	120	76	40-42	180	Painted	1 5/8	165	165	168	76	33	29
122104800322	125	89	43-48	230	Galvanized	1 3/4 - 1 7/8	191	178	190	89	39	45
122104800325	125	89	43-48	230	Painted	1 3/4 - 1 7/8	191	178	190	89	39	45
122105400322	128	95	49-54	280	Galvanized	2 - 2 1/8	216	229	206	102	45	64.5
122105400325	128	95	49-54	280	Painted	2 - 2 1/8	216	229	206	102	45	64.5
122106000322	130	108	55-60	375	Galvanized	2 1/4 - 2 3/8	229	254	225	113	53	88
122106000325	130	108	55-60	375	Painted	2 1/4 - 2 3/8	229	254	225	113	53	88
122106800322	132	121	61-68	425	Galvanized	2 1/2 - 2 5/8	248	273	251	127	60	125
122106800325	132	121	61-68	425	Painted	2 1/2 - 2 5/8	248	273	251	127	60	125
122107500322	135	127	69-75	500	Galvanized	2 3/4 - 2 7/8	279	279	266	133	73	162
122107500325	135	127	69-75	500	Painted	2 3/4 - 2 7/8	279	279	266	133	73	162
122108000322	138	133	76-80	600	Galvanized	3 - 3 1/8	305	286	274	146	76	195
122108000325	138	133	76-80	600	Painted	3 - 3 1/8	305	286	274	146	76	195

122108600322	140	140	81-86	700	Galvanized	3 1/4 - 3 3/8	330	298	286	159	79	224
122108600325	140	140	81-86	700	Painted	3 1/4 - 3 3/8	330	298	286	159	79	224
122109300322	142	152	87-93	750	Galvanized	3 1/2 - 3 5/8	356	318	310	171	83	280
122109300325	142	152	87-93	750	Painted	3 1/2 - 3 5/8	356	318	310	171	83	280
122110200322	144	178	94-102	950	Galvanized	3 3/4 - 4	381	343	352	191	89	378
122110200325	144	178	94-102	950	Painted	3 3/4 - 4	381	343	352	191	89	378
122111500322	146	190	108-115	1,200	Galvanized	4 1/2	460	480	430	208	101	564
122111500325	146	190	108-115	1,200	Painted	4 1/2	460	480	430	208	101	564
122113000322	150	250	122-130	1,400	Galvanized	5	500	500	550	210	120	922
122113000325	150	250	122-130	1,400	Painted	5	500	500	550	210	120	922
122115500322	160	275	140-155	2,000	Galvanized	5 1/2 - 6	580	500	590	230	140	1,295
122115500325	160	275	140-155	2,000	Painted	5 1/2 - 6	580	500	590	230	140	1,295
122116700322	170	290	158-167	2,500	Galvanized	6 1/2	675	600	640	310	160	1,950
122116700325	170	290	158-167	2,500	Painted	6 1/2	675	600	640	310	160	1,950

# Blueprint

