



Superclamp Fixed Jaw Adjustable Girder Clamps

Product information

Fixed jaw adjustable girder clamps are truly versatile in application and may be used for lifting, pulling, or as an anchor point. Designed specifically to provide maximum grab width adjustment. These products are engineered for practical use where mobility is essential. The clamps are speedily applied and do not require additional tools or width adjusting components, such as spacing washers. The left and right-hand threaded adjusting bar ensures a secure grip on the beam flange. Incorporating adjusting mechanism and lifting shackle.

Proof load: 2 x WLL.

Finish: Yellow painted.

Note: All WLL apply to vertical lifting only.

Safety factor: 5:1

Part code	Code	WLL ton	Beam width	A mm	H, mm	J mm	K mm	Weight kg
502300201900060	S1 mm	2	76-190	76-190	22	95	3	4
502300301900060	S2 mm	3	76-190	76-190	22	95	6	5
502300301900061	S2A	3	76-190	76-190	22	95	12.5	8
502300402540060	S3	4	150-254	150-254	22	100	10	11
502300511900060	S3X	5	76-190	76-190	22	105	12.5	10
502300503050060	S3A	5	150-305	150-305	32	105	12.5	15
502300604570060	S4S	6	203-457	203-457	42	105	12.5	18.5
502301004570060	S4A	10	203-457	203-457	42	130	20	28
502301504570060	S12	15	203-457	203-457	50	150	20	49.5
502301506100060	S14	15	406-610	406-610	63	150	20	58.5

Blueprint

