



## Superclamp Swivel Jaw Adjustable Girder Clamps

### Product information

Swivel Jaw Adjustable Girder Clamps incorporate the additional benefit of horizontal jaw adjustment. Incorporating machined jaw, adjusting mechanism and lifting shackle.

This enables the full length and a maximum width of the swivel jaw to anchor evenly on a considerable surface area of the beam flange.

The "Swivel Jaw" range of SUPERCLAMP products are designed to ensure ease of application.

Additional tools or width adjusting components are not required since the left and right hand threaded adjusting bar will adjust to the jaw grip from 89mm to 305mm.

**Proof load:** 2 x WLL.

**Finish:** Yellow painted.

**Note:** All WLL apply to vertical lifting only.

**Safety factor:** 5:1.

Part code	Code	WLL ton	Beam width	A mm	H, mm	J mm	K mm	Weight kg
502300303050080	S5	3	89-305	89-305	25.4	95	6	10
502300303050080	S5A	3	89-305	89-305	25.4	105	10	14
502300503050080	S6	5	89-305	89-305	25.4	105	10	14
502300503050080	S6A	5	89-305	89-305	25.4	105	12.5	15.5
502301003050080	S11	10	89-305	89-305	25.4	130	20	21.5

## Blueprint

