Winch Console-mounted SW-K GAMMA

Product information



Capacity: 200 - 800 kg. Suitable for outdoor use due to robust construction, from 500 kg. load capacity with high-speed gear for small loads and faster winding and unwinding of the unloaded rope.

Features:

- Compact aluminium housing and enclosed sprocket wheel drive. From a capacity of 500 kg with speed increasing ratio for small loads and quicker winding and unwinding of the unloaded rope.
- Spur gear drive for optimal efficiency and comfortable handling.
- Enclosed gear for the protection of parts inside, also for arduous applications.
- Low-friction shaft sliding bearings for improved rope lead-off and a longer service life of the winch.
- Wide rope drum for a large rope capacity with two rope attachment points.
- Easy and quick mounting.
- With integrated safety spring brake system and removable crank. The winches can be operated from either side.


... *Read more*

Material: Aluminium
Marking: According to standard
Standard: EN 13157

© November 2026 - All Rights Reserved

Winch Console-mounted SW-K GAMMA

Blueprint



Technical data

Part code	Code	WLL ton	Rope Ø mm	Capacity 1st layer kg	Capacity top layer kg	A mm	B mm	C mm	D mm	E mm	F mm	Ø G mm mm	Ø H mm mm	L mm	M mm	Weight kg
501300020000930	GAMMA 200	0.2	6	200	110	120	160	192	152	165	135	9.5	50	320	207	6
501300050000930	GAMMA 500	0.5	4	500	200	120	220	330	100	267	125	11	60	250	165	14
501300080000930	GAMMA 800	0.8	7	800	350	200	325	336	180	327	250	14	70	320	207	16

© November 2026 - All Rights Reserved