

Combinations Rope IWRC - TAIFUN

Product information



6-Strand Combination Ropes with steel core (IWRC), the wire strands are covered with PP split film. Blue with white marking yarn in one strand.

Typical applications: Fishing ropes. **Not for lifting.**

[... Read more](#)

Rope construction: See table.

Finish: Galvanized.

Tolerance Ø: -1% to +6%

Combinations Rope IWRC - TAIFUN

Technical data

Part code	Rope diameter	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Lubrication	Weight kg/100m
109800804220029	8	1,570	Galvanized	sZ	15.7	SupplierStandard	9
109801004220029	10	1,570	Galvanized	sZ	25.5	SupplierStandard	15
109801204220029	12	1,570	Galvanized	sZ	31.4	SupplierStandard	20
109801404220029	14	1,570	Galvanized	sZ	45.6	SupplierStandard	28
109801604220029	16	1,570	Galvanized	sZ	60.8	SupplierStandard	37
109801804220029	18	1,570	Galvanized	sZ	74.6	SupplierStandard	46
109802004220029	20	1,570	Galvanized	sZ	95.2	SupplierStandard	59
109802204220029	22	1,570	Galvanized	sZ	139	SupplierStandard	87
109802404220029	24	1,570	Galvanized	sZ	168	SupplierStandard	104
109802604220029	26	1,570	Galvanized	sZ	186	SupplierStandard	117
109802804220029	28	1,570	Galvanized	sZ	212	SupplierStandard	133
109803004220029	30	1,570	Galvanized	sZ	245	SupplierStandard	154
109803204220029	32	1,570	Galvanized	sZ	285	SupplierStandard	178
109803404220029	34	1,570	Galvanized	sZ	303	SupplierStandard	194
109803604220029	36	1,570	Galvanized	sZ	345	SupplierStandard	221
109803804220029	38	1,570	Galvanized	sZ	371	SupplierStandard	242
109804004220029	40	1,570	Galvanized	sZ	402	SupplierStandard	273