

## Lifting chain, grade 80

### Product information



Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

**Material:** Steel

**Marking:** According to standard

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, black

**Standard:** EN 818-2

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

<b>Part code</b>	<b>Chain diameter mm</b>	<b>WLL ton</b>	<b>A mm</b>	<b>B mm</b>	<b>D mm</b>	<b>Weight kg/m</b>
203100600000100	6	1.12	18	9	6	0.8
203100700000100	7	1.5	22	10	7	1.1
203100800000100	8	2	24	12	8	1.35
203101000000100	10	3.15	30	14	10	2.15
203101300000100	13	5.3	39	19	13	3.5
203101600000100	16	8	48	23	16	5.5
203102000000100	20	12.5	60	25	20	8.4
203102200000100	22	15	66	28	22	10.35
203102600000100	26	21.2	78	35	26	15.8
203103200000100	32	31.5	96	43	32	23
203103600000100	36	40	108	49	36	29
203104000000100	40	50	120	54	40	36

## Blueprint

