Master link, grade 80

Product information



Masterlink for chain sling assemblies.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-4
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Master link, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
4011NOR76	1.6	110	6/7	6	110	60	13	0.34
4011NOR87	2.12	110	8	7	110	60	16	0.53
4011NOR108	3.15	135	10	8	135	75	18	0.8
4011NOR1310	5.3	160	13	10	160	90	22	1.5
4011NOR1613	8	180	16	13	180	100	26	2.3
4011NOR1816	11.2	200	18	16	200	110	32	3.9
4011NOR2218	14	260	20	18	260	140	36	6.35
4011NOR2220	17	300	22	20	300	160	40	9
4011NOR2622	21.2	340	26	22	340	180	45	12.8
4011NOR3226	31.5	350	32	26	350	190	50	17.2
4011NOR3632	45	400	36	32	400	200	56	24.2

© November 2026 - All Rights Reserved