

## D Shackle High Tensile SS, Type A

### Product information



Excellent for general lifting applications - high tensile properties while avoiding work hardening. Thick lugs on the shackle pins ensure that the product is both durable and dependable. Manufactured using the latest technology in electrical upset forging.

- Every shackle is proof load tested to 2 x WLL and certified at our manufacturing facility in the North East of England
- All shackles are manufactured in accordance with the Machine Directive 2006/42/EC
- Inspection certificate BS EN 10204 3.1 available on request
- High quality finish and excellent polish

**Material:** Stainless steel

**Safety factor:** 6:1

<b>Part code</b>	<b>WLL ton</b>	<b>P mm</b>	<b>B mm</b>	<b>J mm</b>	<b>L</b>	<b>Weight kg</b>
420100102710	1	10	8	16	32	0.085
420100202710	2	12.7	10	20	40	0.15
420100302710	3	16	12.7	25	50	0.35
420100502710	5	19	16	32	64	0.55
420100702710	7	22.2	19	38	76	1
420100902710	9	25.4	22.2	44	88	1.9
420101102710	11	28.6	25.4	51	102	2.9
420101302710	13	31.8	28.6	57	114	3.1
420101502710	15	34.9	31.8	64	128	4.35
420101802710	18	38	34.9	76	152	5.3

# Blueprint

