# Master Link Sub-Assembly CAKS Stainless

## Product information



- Made of high quality duplex steel (AISI318LN)
- Outstanding corrosion resistance
- The CAGF master link offers enough space to guide two ropes per transition link. This makes it ideal for 3- and 4-leg rope slings.

... *Read more*


**Material:** AISI318LN
**Temperature range:** -40°C up to 250°C

**Safety factor:** 4:1

© November 2026 - All Rights Reserved

# Master Link Sub-Assembly CAKS Stainless

## Blueprint




## Technical data

| Part code | WLL ton | WLL 45- 60° ton | b mm | d mm | t mm | Weight kg |
|---|---|---|---|---|---|---|
| 400100180130 | 1.8 | 1.25 | 60-60 | 16-13 | 110-110 | 1.21 |
| 400100240130 | 2.4 | 1.7 | 60-60 | 16-16 | 110-110 | 1.59 |
| 400100330130 | 3.25 | 2.25 | 75-60 | 18-16 | 135-110 | 1.86 |
| 400100500130 | 5 | 3.5 | 90-75 | 22-18 | 160-135 | 3.1 |
| 400100850130 | 8.5 | 5.95 | 100-90 | 26-22 | 180-160 | 5.3 |
| 400101080130 | 10.75 | 7.5 | 110-100 | 32-26 | 200-180 | 8.5 |
| 400101360130 | 13.6 | 9.5 | 140-110 | 36-32 | 260-200 | 14.15 |

© November 2026 - All Rights Reserved