



## Master Link CAGF/CBGF, 1- and 2-leg Stainless

### Product information

These master links have a flattened section to allow the use of connectors

(e.g. clevis shackles type CGS).

- Made of high quality duplex steel (AISI318LN)
- Outstanding corrosion resistance
- Use among other things for 1- and 2-leg chain slings

**Material:** AISI318LN

**Temperature range:** -40°C up to 250°C

**Finish:** Blasted

**Safety factor:** 4:1

**Grade:** 6

Part code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	b mm	d mm	t mm	Weight kg
400100630140	0.63	5	4	50	10	80	0.15
400100160140	1.55	-	-	25	10	44	0.092
400100160140	1.55	6/7/8	5/6	60	13	110	0.34
400100250140	2.45	-	-	25	13	54	0.195
400100250140	2.45	10	7/8	60	16	110	0.53
400100360140	3.55	-	10	75	18	135	0.8
400100390140	3.85	-	-	34	16	70	0.37
400100600140	6	-	-	40	18	85	0.53
400100600140	6	13/16	13	90	22	160	1.5
400100760140	7.6	-	-	50	22	115	1.065
400100800140	8	18	16	100	26	180	2.3
400100960140	9.6	-	-	65	26	140	1.825
400101200140	12	20	18	110	32	200	3.9
400101600140	16	-	20	140	36	260	6.35

## Blueprint

