Master Link CAGF, 1- and 2-leg Stainless

Product information



These master links have a flattened section to allow the use of connectors (e.g. clevis shackles type CGS).

- Made of high quality duplex steel (AISI318LN)
- Outstanding corrosion resistance
- Use among other things for 1- and 2-leg chain slings

... *Read more*


Material: AISI318LN
Temperature range: -40°C up to 250°C
Finish: Blasted

Safety factor: 4:1
Grade: 6

© November 2026 - All Rights Reserved

Master Link CAGF, 1- and 2-leg Stainless

Blueprint



Technical data

Part code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	b mm	d mm	t mm	Weight kg
400100630140	0.63	5	4	50	10	80	0.15
400100160140	1.55	6/7/8	5/6	60	13	110	0.34
400100250140	2.45	10	7/8	60	16	110	0.53
400100360140	3.55	-	10	75	18	135	0.8
400100600140	6	13/16	13	90	22	160	1.5
400100800140	8	18	16	100	26	180	2.3
400101200140	12	20	18	110	32	200	3.9
400101600140	16	-	20	140	36	260	6.35
-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-

© November 2026 - All Rights Reserved