Lifting Eye RUD VWBG-V - with variable length

Product information



- Rotating 360°, pivoting 230°
- Optical markings for easy determination for withdraw from service
- Ball bearing

... *Read more*

Temperature range: -40°C up to 100°C

Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Eye RUD VWBG-V - with variable length

Blueprint



Technical data

Part code	WLL ton	Thread mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	T mm
42158600330	0.3	M8	8	31	29	30	27	8-102	36	M8	76
42158600331	0.45	M10	8	31	29	33.5	30	10-122	38	M10	78
42158600332	0.6	M12	10	49	35	42	36	12-140	47	M12	107
42158600337	1	M14	13	46	38	48	41	14-160	56	M14	114
42158600333	1.3	M16	13	46	38	48	41	16-180	56	M16	114
42158600338	1.8	M18	13	54	35	62	55	18-83	67	M18	137
42158600334223	2	M20	13	54	35	62	55	20-223	67	M20	137
4215860033494	2	M22	13	54	35	62	55	22-94	67	M22	137
42158600335255	3.5	M24	18	66	40	81	70	24-255	88	M24	173
4215860033592	3.5	M27	18	66	40	81	70	27-92	88	M27	173
42158600336	5	M30	22	90	50	99	85	30-330	106	M30	221

© November 2026 - All Rights Reserved