

## Bow Shackle No 854, Gunnebo - Screw Pin



### Product information

**Approved according to:** DNV 2.7-1

**Forging tolerances:** +5% on inside width/length.

**Material:** High tensile steel, quenched and tempered.

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to 200°C

**Finish:** All parts hot dip galvanized, brown painted bolts/pins on top of galv.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271

**Safety factor:** 6:1

**Grade:** 6

Part code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	e mm	Weight kg
420100050400	0.5	12	29	1/4" - 6	8	16	20	0.06
420100750400	0.75	13	32	5/16" - 8	10	20	21	0.11
420100100400	1	16	36	3/8" - 9	11	22	26	0.15
420100150400	1.5	18	43	7/16" - 11	13	26	29	0.21
420100200400	2	21	47	1/2" - 13	16	33	33	0.37
420100330400	3.25	27	60	5/8" -16	19	40	42	0.65
420100480400	4.75	31	71	3/4" - 19	22	48	49	1.1
420100650400	6.5	37	84	7/8" - 22	25	52	60	1.5
420100850400	8.5	43	95	1" - 25	28	60	68	2.21
420100950400	9.5	46	108	1 1/8" - 28	32	64	74	3.1
420101200400	12	52	119	1 1/4" -32	35	72	83	4.2
420101350400	13.5	57	132	1 3/8" - 35	38	76	89	6
420101700400	17	60	146	1 1/2" - 38	42	84	98	8
420102500400	25	74	178	1 3/4" - 45	50	105	127	13.5
420103500400	35	83	197	2" - 50	57	112	138	19
420105500400	55	105	260	2 1/2" - 65	70	145	180	38

# Blueprint

