Dee Shackle No 834, Gunnebo - Screw Pin

Product information



Approved according to: DNV 2.7-1

Forging tolerances:+-5% on inside width/length.

... *Read more*


Material: High tensile steel, quenched and tempered.
Marking: According to standard, CE-mark
Temperature range: -20°C up to 200°C
Finish: All parts hot dip galvanized, brown painted bolts/pins on top of galv.
Standard: EN 13889, US. FED. SPEC. RR-C-271

Safety factor: 6:1
Grade: 6

© November 2026 - All Rights Reserved

Dee Shackle No 834, Gunnebo - Screw Pin

Blueprint



Technical data

Part code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	Weight kg
420100030390	0.33	10	22	5	6	13	0.02
420100050390	0.5	12	25	7	8	12	0.06
420100750390	0.75	13.5	27	9	10	16	0.11
420100100390	1	17	31	10	11	20	0.15
420100150390	1.5	18.5	37	11	13	22	0.21
420100200390	2	21	41	13	16	33	0.25
420100330390	3.25	27	51	16	19	40	0.55
420100480390	4.75	31	60	19	22	48	1
420100650390	6.5	37	71	22	25	52	1.3
420100850390	8.5	43	81	25	28	60	1.9
420100950390	9.5	46	90	28	32	64	2.8
420101200390	12	52	100	32	35	72	3.6
420101350390	13.5	57	111	35	38	76	4.6
420101700390	17	60	122	38	42	84	6.5
420102500390	25	74	149	45	50	105	11.5

© November 2026 - All Rights Reserved