

Shackle Crosby S-2135

Product information



- Trusted Crosby quality.
- Embossed Angle Indicators included.
- Individually proof loaded to 2 times the Working Load Limit

... [Read more](#)


Temperature range: -20°C up to +200°C

Safety factor: 5:1

Grade: 8

Shackle Crosby S-2135

Blueprint



Technical data

| Part code | WLL ton | A mm | B mm | C mm | D mm | D2mm mm | E mm | F mm | +/-0 mm | Weight kg |
|--------------|---------|------|------|------|------|---------|------|------|---------|-----------|
| 420108501540 | 85 | 127 | 83 | 330 | 85 | 80 | 190 | 162 | +6/-0 | 77 |
| 420112001540 | 120 | 144 | 95 | 380 | 95 | 89 | 238 | 200 | +6/-0 | 114 |
| 420115001540 | 150 | 165 | 108 | 385 | 105 | 100 | 275 | 230 | +8/-0 | 161 |
| 420120001540 | 200 | 180 | 125 | 450 | 120 | 110 | 280 | 270 | +8/-0 | 238 |
| 420125001540 | 250 | 205 | 140 | 520 | 130 | 115 | 305 | 290 | +10/-0 | 304 |
| 420130001540 | 300 | 205 | 150 | 530 | 140 | 120 | 305 | 315 | +10/-0 | 365 |
| 420140001540 | 400 | 230 | 175 | 575 | 160 | 160 | 325 | 365 | +10/-0 | 597 |
| 420150001540 | 500 | 250 | 185 | 650 | 180 | 160 | 350 | 385 | +12/-0 | 729 |
| 420160001540 | 600 | 275 | 205 | 650 | 200 | 185 | 375 | 430 | +13/-0 | 961 |
| 420170001540 | 700 | 300 | 215 | 650 | 210 | 200 | 400 | 440 | +15/-0 | 1,082 |
| 420180001540 | 800 | 300 | 220 | 650 | 210 | 200 | 400 | 450 | +15/-0 | 1,097 |
| 420110001541 | 1,000 | 340 | 240 | 700 | 240 | 240 | 420 | 500 | +17/-0 | 1,464 |
| 420112501541 | 1,250 | 360 | 270 | 750 | 260 | 225 | 450 | 570 | +18/-0 | 1,940 |
| 420115001541 | 1,500 | 360 | 290 | 800 | 280 | 225 | 450 | 610 | +18/-0 | 2,309 |