

Shackle Crosby S-2135



Product information

- Trusted Crosby quality.
- Embossed Angle Indicators included.
- Individually proof loaded to 2 times the Working Load Limit

Marking: According to standard

Temperature range: -20°C up to +200°C

Standard: EN 10204

Safety factor: 5:1

Grade: 8

Part code	WLL ton	A mm	B mm	C mm	D mm	D2 mm	E mm	F mm	+/-0	Weight kg
420108501540	85	127	83	330	85	80	190	162	+6/-0	77
420112001540	120	144	95	380	95	89	238	200	+6/-0	114
420115001540	150	165	108	385	105	100	275	230	+8/-0	161
420120001540	200	180	125	450	120	110	280	270	+8/-0	238
420125001540	250	205	140	520	130	115	305	290	+10/-0	304
420130001540	300	205	150	530	140	120	305	315	+10/-0	365
420140001540	400	230	175	575	160	160	325	365	+10/-0	597
420150001540	500	250	185	650	180	160	350	385	+12/-0	729
420160001540	600	275	205	650	200	185	375	430	+13/-0	961
420170001540	700	300	215	650	210	200	400	440	+15/-0	1,082
420180001540	800	300	220	650	210	200	400	450	+15/-0	1,097
420110001541	1,000	340	240	700	240	240	420	500	+17/-0	1,464
420112501541	1,250	360	270	750	260	225	450	570	+18/-0	1,940
420115001541	1,500	360	290	800	280	225	450	610	+18/-0	2,309

Blueprint

