

Pillar Jib Crane - Overbraced

Product information



The PFT's beam is built on an I beam profile, appropriate for indoor or outdoor use. Its light weight gives it great flexibility for rotations of 270°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

A full range of accessories is available.

Floor fixing is done with chemical anchors or anchor rods with foundation.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind).
- Hoist power supply cable.
- Lockable main switch.
- Rotation slowing device (adaptable without welding or mechanical intervention).
- Hot dip galvanizing (contact us).
- Rotation stops to weld onto the assembly, or adjustable.
- Single or multiposition's rotation lock.
- Electric or manual hoist.
- Outdoor use.

... [Read more](#)

Pillar Jib Crane - Overbraced

Technical data

Part code	WLL ton	Length m	Cap. kg
6025PFT00152000	0.15	2	150
6025PFT00152500	0.15	2.5	150
6025PFT00153000	0.15	3	150
6025PFT00153500	0.15	3.5	150
6025PFT00154000	0.15	4	150
6025PFT00154500	0.15	4.5	150
6025PFT00155000	0.15	5	150
6025PFT00155500	0.15	5.5	150
6025PFT00156000	0.15	6	150
6025PFT00156500	0.15	6.5	150
6025PFT00157000	0.15	7	150
6025PFT00252000	0.25	2	250
6025PFT00252500	0.25	2.5	250
6025PFT00253000	0.25	3	250
6025PFT00253500	0.25	3.5	250
6025PFT00254000	0.25	4	250
6025PFT00254500	0.25	4.5	250
6025PFT00255000	0.25	5	250
6025PFT00255500	0.25	5.5	250
6025PFT00256000	0.25	6	250
6025PFT00256500	0.25	6.5	250
6025PFT00257000	0.25	7	250
6025PFT00502000	0.5	2	500
6025PFT00502500	0.5	2.5	500
6025PFT00503000	0.5	3	500
6025PFT00503500	0.5	3.5	500
6025PFT00504000	0.5	4	500
6025PFT00504500	0.5	4.5	500
6025PFT00505000	0.5	5	500
6025PFT00505500	0.5	5.5	500
6025PFT00506000	0.5	6	500

Pillar Jib Crane - Overbraced

Technical data

Part code	WLL ton	Length m	Cap. kg
6025PFT00506500	0.5	6.5	500
6025PFT00507000	0.5	7	500
6025PFT01002000	1	2	1,000
6025PFT01002500	1	2.5	1,000
6025PFT01003000	1	3	1,000
6025PFT01003500	1	3.5	1,000
6025PFT01004000	1	4	1,000
6025PFT01004500	1	4.5	1,000
6025PFT01005000	1	5	1,000
6025PFT01005500	1	5.5	1,000
6025PFT01006000	1	6	1,000
6025PFT01006500	1	6.5	1,000
6025PFT01007000	1	7	1,000
6025PFT01602000	1.6	2	1,600
6025PFT01602500	1.6	2.5	1,600
6025PFT01603000	1.6	3	1,600
6025PFT01603500	1.6	3.5	1,600
6025PFT01604000	1.6	4	1,600
6025PFT01604500	1.6	4.5	1,600
6025PFT01605000	1.6	5	1,600
6025PFT02002000	2	2	2,000
6025PFT02002500	2	2.5	2,000
6025PFT02003000	2	3	2,000
6025PFT02003500	2	3.5	2,000
6025PFT02004000	2	4	2,000
6025PFT02004500	2	4.5	2,000
6025PFT02005000	2	5	2,000