



Pillar Jib Crane - Underbraced

Product information

The headroom is the main asset of the PFI. Its I beam profile allows to consider installation of a hoist with electric or manual steering. Floor fixing is effected by chemical anchors or anchor rods with foundation. A full range of accessories is available.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind)
- Hoist power supply cable
- Lockable main switch
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly, or adjustable
- Single or multipositions rotation lock
- Outdoor use
- Electric or manual hoist

Part code	WLL ton	Length m	Cap. kg
6025PFI00152000	0.15	2	150
6025PFI00152500	0.15	2.5	150
6025PFI00153000	0.15	3	150
6025PFI00153500	0.15	3.5	150
6025PFI00154000	0.15	4	150
6025PFI00154500	0.15	4.5	150

6025PFI00155000	0.15	5	150
6025PFI00155500	0.15	5.5	150
6025PFI00156000	0.15	6	150
6025PFI00156500	0.15	6.5	150
6025PFI00157000	0.15	7	150
6025PFI00252000	0.25	2	250
6025PFI00252500	0.25	2.5	250
6025PFI00253000	0.25	3	250
6025PFI00253500	0.25	3.5	250
6025PFI00254000	0.25	4	250
6025PFI00254500	0.25	4.5	250
6025PFI00255000	0.25	5	250
6025PFI00255500	0.25	5.5	250
6025PFI00256000	0.25	6	250
6025PFI00256500	0.25	6.5	250
6025PFI00257000	0.25	7	250
6025PFI00502000	0.5	2	500
6025PFI00502500	0.5	2.5	500
6025PFI00503000	0.5	3	500
6025PFI00503500	0.5	3.5	500
6025PFI00504000	0.5	4	500
6025PFI00504500	0.5	4.5	500
6025PFI00505000	0.5	5	500

6025PFI00505500	0.5	5.5	500
6025PFI00506000	0.5	6	500
6025PFI00506500	0.5	6.5	500
6025PFI00507000	0.5	7	500
6025PFI01002000	1	2	1,000
6025PFI01002500	1	2.5	1,000
6025PFI01003000	1	3	1,000
6025PFI01003500	1	3.5	1,000
6025PFI01004000	1	4	1,000
6025PFI01004500	1	4.5	1,000
6025PFI01005000	1	5	1,000
6025PFI01005500	1	5.5	1,000
6025PFI01006000	1	6	1,000
6025PFI01602000	1.6	2	1,600
6025PFI01602500	1.6	2.5	1,600
6025PFI01603000	1.6	3	1,600
6025PFI01603500	1.6	3.5	1,600
6025PFI01604000	1.6	4	1,600
6025PFI01604500	1.6	4.5	1,600
6025PFI01605000	1.6	5	1,600
6025PFI02002000	2	2	2,000
6025PFI02002500	2	2.5	2,000
6025PFI02003000	2	3	2,000

6025PFI02003500	2	3.5	2,000
6025PFI02004000	2	4	2,000
6025PFI02004500	2	4.5	2,000
6025PFI02005000	2	5	2,000