

Connecting Link Green Pin Tycan® UMJT

Product information



The Green Pin Tycan® Connecting Link GR10 is used for connecting Green Pin Tycan® chain slings. The Connecting Link is made from grade 10, high tensile steel and is available in a range with a working load limit from 2.6 ton up to 10.3 ton and a lashing capacity of 10 and 13.6 ton. Spare bushes for the connecting link are also available separately.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb

[... Read more](#)

Material: Alloy steel

Marking: According to standard, Manufacturer ID, chain diameter, traceability code, steel grade, item code and origin

Temperature range: -40°C up to +200°C

Finish: Blue painted


Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Connecting Link Green Pin Tycan® UMJT

Blueprint



Technical data

| Part code | WLL ton | LC kN | For chain Ø mm | a mm | b mm mm | c mm | d mm mm | e mm mm | f mm mm | g mm mm | h mm mm | Weight kg |
|--------------|---------|-------|----------------|------|---------|------|---------|---------|---------|---------|---------|-----------|
| 402200260220 | 2.6 | 54 | 11x15 | 9 | 57 | 14 | 20 | 55 | 16 | 19 | 13 | 0.22 |
| 402200400220 | 4 | 80 | 11x20 | 12 | 66 | 18 | 23 | 64 | 18 | 23 | 16 | 0.37 |
| 402200680220 | 6.8 | 136 | 13x30 | 16 | 83 | 21 | 32 | 85 | 24 | 28 | 20 | 0.78 |
| 402201030220 | 10.3 | 206 | - | 19 | 103 | 25.5 | 40 | 107.5 | 28 | 34 | 24 | 1.46 |