

Cable grip – Single (K1)

Product information

These grips offer a flexible eye with double weave galvanized wire construction for general duty applications. Standard fitted lengths of 600mm or 900mm are suitable for most applications, special grips to order.

[... Read more](#)

Finish: Galvanized.

Note: A minimum safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling is recommended.



Cable grip – Single (K1)

Technical data

| Part code | Code | Rope Ø range mm | MBL ton | L mm | Weight kg |
|--------------|--------|--------------------|------------|------|--------------|
| 140601000010 | 106/6 | 6-10 | 1.5 | 600 | 0.12 |
| 140602000010 | 106/10 | 10-20 | 1.86 | 600 | 0.17 |
| 140602000011 | 109/10 | 10-20 | 1.86 | 900 | 0.17 |
| 140603000011 | 109/20 | 20-30 | 2.26 | 900 | 0.2 |
| 140603000010 | 106/20 | 20-30 | 2.26 | 600 | 0.22 |
| 140603800011 | 109/25 | 25-38 | 3.7 | 900 | 0.29 |
| 140604000010 | 106/30 | 30-40 | 3.7 | 600 | 0.29 |
| 140605000010 | 106/40 | 40-50 | 5.49 | 600 | 0.63 |
| 140605000011 | 109/40 | 40-50 | 5.49 | 900 | 0.95 |
| 140606500010 | 106/50 | 50-65 | 5.49 | 600 | 0.65 |
| 140608000010 | 109/65 | 65-80 | 7.32 | 900 | 1.2 |
| 140609500010 | 109/80 | 80-95 | 7.32 | 900 | 1.3 |
| 140611000010 | 109/95 | 95-110 | 10.61 | 900 | 2.1 |