

## Cablegrip Open

### Product information



**General:** Open Ended Cablegrip ideal for joining two cables to form a continuous loop. Typical application: replacement of elevator cables, where the old cable would be attached to the new one, and the cable then fed round with ease.

**Design:** Pleated of double wire ropes.

**Material:** Steel wire rope - Galvanized.

**Note:** Substantial safety ratios have been applied to all quoted minimum-breaking strengths. Additional safety factors, determined by application, should be applied. CERTEX recommends a minimum saf

Part code	Code	Rope Ø range mm	MBL	Length mm	Weight kg
140601600020	KO-0	8-16	1,504	1,200	0.25
140602000020	KO-1	10-20	1,860	1,200	0.3
140602000021	KO-10	10-20	1,860	1,800	0.45
140603000020	KO-2	20-30	2,256	1,200	0.35
140603000021	KO-11	20-30	2,256	1,800	0.5
140603800021	KO-19	25-38	3,696	1,800	0.82
140604000020	KO-3	30-40	3,696	1,200	0.64
140604000021	KO-12	30-40	3,696	1,800	0.82
140605000020	KO-4	40-50	5,490	1,200	1
140606500020	KO-5	50-65	5,490	1,200	1.1
140606500021	KO-14	50-65	5,490	1,800	1.6
140608000020	KO-15	65-80	7,320	1,800	2.2
140609500020	KO-16	80-95	9,150	1,800	2.3
140611000020	KO-17	95-110	12,736	1,800	4.4