# Chain Block KITO M3

## Product information




KITO M3 Series Chain Hoists are built with premium grade components for long life in demanding industrial and contracting applications. M3 lever hoists feature double-reduction gearing for reduced size and weight.
Safe, reliable mechanical brake activates instantly, holds the load securely.
Double reduction gearing for a smaller hoist that requires minimum power to operate.
Spring loaded free-wheel for fast, easy load chain free-wheeling.
Open load sheave allows easy inspection and cleaning without dismantling the unit
Maintenance free sealed gears and brake protected against damage from dust and water.

... *Read more*

**Material:** High inpact steel housing, chain grade 10.
**Marking:** According to standard, CE-mark, WLL, code.
**Temperature range:** -40ºC up to +60ºC
**Finish:** Painted.
**Standard:** AS 1418.2

**Safety factor:** 4:1

© November 2026 - All Rights Reserved

# Chain Block KITO M3

## Blueprint




## Technical data

| Part code | WLL ton | Lifting height m | Number of falls | Load chain mm | a mm | b mm | d mm | e mm | f mm | g mm | s mm | t mm | u mm mm | v mm mm | w mm mm | x mm mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 500100050250050 | 0.5 | 2.5 | 1 | 5 | 158 | 161 | 2,500 | 69 | 99 | 27 | 35.5 | 12.1 | 17 | 77 | 35 | 89 | 10 |
| 500100050600050 | 0.5 | 6 | 1 | 5 | 158 | 161 | 2,500 | 69 | 99 | 27 | 35.5 | 12.1 | 17 | 77 | 35 | 89 | 10 |
| 500100050300050 | 0.5 | 3 | 1 | 5 | 158 | 161 | 2,500 | 69 | 99 | 27 | 35.5 | 12.1 | 17 | 77 | 35 | 89 | 10 |
| 500100100250050 | 1 | 2.5 | 1 | 6,3 | 162 | 161 | 2,500 | 71 | 99 | 29 | 42.5 | 16 | 21.8 | 93 | 41 | 101 | 11.5 |
| 500100100450050 | 1 | 4.5 | 1 | 6.3 | 162 | 161 | 2,500 | 71 | 99 | 29 | 42.5 | 16 | 21.8 | 93 | 41 | 101 | 11.5 |
| 500100100300050 | 1 | 3 | 1 | 6.3 | 162 | 161 | 2,500 | 71 | 99 | 29 | 42.5 | 16 | 21.8 | 93 | 41 | 101 | 11.5 |
| 500100100600050 | 1 | 6 | 1 | 6.3 | 162 | 161 | 2,500 | 71 | 99 | 29 | 42.5 | 16 | 21.8 | 93 | 41 | 101 | 11.5 |
| 500100100600054 | 1 | 6 | 1 | 6.3 | 162 | 161 | 2,500 | 71 | 99 | 29 | 42.5 | 16 | 21.8 | 93 | 41 | 101 | 11.5 |
| 500100150250050 | 1.5 | 2.5 | 1 | 7,1 | 171 | 182 | 2,500 | 78 | 112 | 34 | 47.5 | 19.5 | 26.5 | 106 | 47 | 119 | 14.5 |
| 500100200300050 | 2 | 3 | 1 | 8 | 185 | 202 | 3,000 | 87 | 125 | 36 | 50 | 21.8 | 30 | 116 | 49 | 124 | 20 |
| 500100200600054 | 2 | 6 | 1 | 8 | 182 | 202 | 3,000 | 87 | 125 | 36 | 50 | 21.8 | 30 | 116 | 49 | 124 | 20 |
| 500100200300051 | 2 | 3 | 1 | 8 | 182 | 202 | 3,000 | 87 | 125 | 36 | 50 | 21.8 | 30 | 116 | 49 | 124 | 21 |
| 500100200450050 | 2 | 4.5 | 1 | 8 | 182 | 202 | 3,000 | 87 | 125 | 36 | 50 | 21.8 | 30 | 116 | 49 | 124 | 23.45 |
| 500100300300050 | 3 | 3 | 2 | 7,1 | 171 | 235 | 3,100 | 78 | 162 | 42.5 | 56 | 27.2 | 37.5 | 138 | 57 | 148 | 24 |
| 500100300600050 | 3 | 6 | 2 | 7,1 | 171 | 235 | 3,100 | 78 | 162 | 42.5 | 56 | 27.2 | 37.5 | 138 | 57 | 148 | 24 |
| 500100300600054 | 3 | 6 | 2 | 7,1 | 171 | 235 | 3,100 | 78 | 162 | 42.5 | 56 | 27.2 | 37.5 | 138 | 57 | 148 | 24 |
| 500100500300050 | 5 | 3 | 2 | 9 | 192 | 282 | 3,600 | 91 | 194 | 46.5 | 63 | 34.5 | 47.5 | 161 | 67.5 | 172 | 41 |
| 500100500600050 | 5 | 6 | 2 | 9 | 192 | 282 | 3,600 | 91 | 194 | 46.5 | 63 | 34.5 | 47.5 | 161 | 67.5 | 172 | 41 |
| 500100500300051 | 5 | 3 | 2 | 9 | 192 | 282 | 3,600 | 91 | 194 | 46.5 | 63 | 34.5 | 47.5 | 161 | 67.5 | 172 | 41 |
| 500100500600054 | 5 | 6 | 2 | 9 | 192 | 282 | 3,600 | 91 | 194 | 46.5 | 63 | 34.5 | 47.5 | 161 | 67.5 | 172 | 41 |
| 500100750300050 | 7.5 | 3 | 3 | 9 | 192 | 373 | 4,200 | 91 | 253 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 275 | 63 |
| 500100750600050 | 7.5 | 6 | 3 | 9 | 192 | 373 | 4,200 | 91 | 253 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 275 | 63 |

© November 2026 - All Rights Reserved

# Chain Block KITO M3

## Technical data

| Part code | WLL ton | Lifting height m | Number of falls | Load chain mm | a mm | b mm | d mm | e mm | f mm | g mm | s mm | t mm | u mm mm | v mm mm | w mm mm | x mm mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 500101000350050 | 10 | 3.5 | 4 | 9 | 192 | 438 | 4,200 | 111 | 308 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 295 | 83 |
| 500101000500050 | 10 | 5 | 4 | 9 | 192 | 438 | 4,200 | 111 | 308 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 295 | 83 |
| 500101000300051 | 10 | 3 | 4 | 9 | 192 | 438 | 4,200 | 111 | 308 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 295 | 83 |
| 500101000600051 | 10 | 6 | 4 | 9 | 192 | 438 | 4,200 | 111 | 308 | 72.5 | 85 | 47.5 | 63 | 231 | 97.5 | 295 | 83 |
| 500101500350050 | 15 | 3.5 | 6 | 9 | 268 | 492 | 4,700 | 119 | 337 | 80 | 100 | 60 | 80 | 275 | 110 | 320 | 155 |
| 500102000350050 | 20 | 3.5 | 8 | 9 | 374 | 746 | 4,800 | 187 | 373 | 81 | 110 | 67 | 90 | 301 | 125 | 351 | 235 |
| 500103000350050 | 30 | 3.5 | 10 | 9 | 404 | 746 | 4,800 | 202 | 373 | 103 | 125 | 85 | 112 | 367 | 143 | 400 | 310 |
| 500104000350050 | 40 | 3.5 | 14 | 9 | 502 | 760 | 4,900 | 251 | 380 | 96 | 145 | 123 | 133 | 412.5 | 182.5 | 445 | 480 |
| 500105000350050 | 50 | 3.5 | 16 | 9 | 544 | 796 | 4,900 | 272 | 398 | 100 | 165 | 135 | 155 | 447.5 | 202.5 | 467 | 640 |

© November 2026 - All Rights Reserved