Manual Chain Hoist KITO ATEX Medium

Product information



Manual chain Hoist ATEX Medium from KITO

- Equipment classification Gas II 2G EX h IIB T3 Gb (zone 1)
- Equipment classification Dust II 2D EX h IIIB T200°C Db (zone 21)
- Impact resistant housing
- Double pawl spring
- Highly accurate and durable gear mechanism
- Double brake enclose keeping out rainwater and dust
- Mechanical load brake
- Low pulling force on the hand chain
- Overload protection by slipping clutch

Exposion Protected: Equipment is executed with non-sparking materials for fast mechanical contact parts for hand chain movements and internal fast moving hoist parts, extended with unique and reliable bronze coated load hooks. ... *Read more*

Marking: According to standard, CE-mark
Temperature range: -40°C up to +40°C
Finish: Powercoat
Standard: EN 13157

© November 2026 - All Rights Reserved

Manual Chain Hoist KITO ATEX Medium

Blueprint



Technical data

Part code	Code	WLL ton	Lifting height m	Number of falls	Headroom mm	Load chain mm	A mm	B mm	D mm	E mm	F mm	F1 mm mm	Weight kg
500100100300410	K010	1	3	1	295	6.3	91	71	99	62	34.6	29	11.5
500100200300410	K020	2	3	1	375	8	95	87	125	77	40	36	20

© November 2026 - All Rights Reserved