



Manual Chain Hoist KITO CX Series

Product information

The KITO chain block CX has a light-weight aluminium housing, and is the size of a coaster. The hooks are suitable for a larger intake and its compact measures enables maximum lifting height. Flush-mounted screws at the housing reduce the injury risk. The standard chain block is equipped with an overload protection.

Material: High impact aluminium housing, nickel-plated load chain in grade 10.

Marking: Type plate with WLL, CE-marking and serial number.

Finish: Surface treated aluminium.

Safety factor: 4:1

Part code	Code	WLL ton	Lifting height m	Number of falls	Load chain mm	Hand force max. kg	Hand chain length m	Weight kg
500100030200300	CX003	0.25	2	1	3,2 x 9,0	14,7	-	2
500100030250300	CX003	0.25	2.5	1	3,2 x 9,0	14,7	-	2.2
500100030300300	CX003	0.25	3	1	3,2 x 9,0	14,7	-	2.4
500100030300305	CX003	0.25	3	1	3,2 x 9,0	14,7	6	2.4
500100030500307	CX003	0.25	5	1	3,2 x 9,0	14,7	-	3.2
500100030600300	CX003	0.25	6	1	3,2 x 9,0	14,7	-	3.6
500100031000306	CX003	0.25	10	1	3,2 x 9,0	14,7	-	5.2
500100050250300	CX005	0.5	2.5	1	4,3 x 12,1	18,6	-	4.05
500100050300300	CX005	0.5	3	1	4,3 x 12,1	18,6	6	4.5
500100050300305	CX005	0.5	3	1	4,3 x 12,1	18,6	-	4.5
500100100300300	CX010	1	3	2	4,3 x 12,0	19,3	-	7.3

Blueprint

