# Low Speed Electric Winch LS5000

**Product information**




A low-speed electric winch, made to move fragile loads from 0,3 metres per minute, powerful with its 5 ton lifting capacity in combination with a 230V connection.

- robust and safe electric pulling and lifting winch 400 V / 230 V
- protection classification electric IP55 / mechanical IP54
- mechanical overload protection
- thermal protection electric motor
- low voltage (24 V) pendant switch with 2 m cable
- including 2 m power cable with 16A CEE plug
- automatic grease system for the worm gearing
- 1 layer of paint

**Options:**

- limit switch - required for lifting applications (LS)
- grooved drum (GD)
- 230V - 50Hz


... *Read more*

**Material:** Steel
**Marking:** According to standard, CE-mark
**Temperature range:** - 20°C up to + 40°C
**Finish:** Painted, light grey
**Standard:** EN 14492
**Note:** Steel wire ropes must be ordered separately

© November 2026 - All Rights Reserved

# Low Speed Electric Winch LS5000

## Blueprint



## Technical data

| Part code | Code | WLL ton | Lifting speed m/min | Rope Ø mm | Motor kW | Rope capacity m | Capacity top layer kg | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm | L mm | M mm | N mm | P mm | R mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 540677600050 | LS5000 | 5 | 0,4 | 18 | 0.75 | 39 | 3,959 | 730 | 704 | 630 | 600 | 169 | 534 | 183 | 322 | 219 | 25 | 351 | 126 | 254 | 427 | 255 | 216 |

© November 2026 - All Rights Reserved