Spur Gear Hand Winch TL300-600 EV Zinc Plated

Product information



This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semi-closed housing. In short, a fine, easy winch!

- robust and safe lifting and pulling winch
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards
- adjustable crank
- suitable for wall mounting
- zinc-plated finish 6 - 8 micron (EV)

Options:

- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
  CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
  CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -20°C up to +70°C
Finish: Zinc Plated
Standard: EN 13157
Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

© November 2026 - All Rights Reserved

Spur Gear Hand Winch TL300-600 EV Zinc Plated

Blueprint



Technical data

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight kg
501300030001020	TL300 EV	0.3	4	35.4	300	172	10
501300060001020	TL600 EV	0.6	6	12.3	600	336	11

© November 2026 - All Rights Reserved