

Lifting Point Pewag PLZW Zeta

Product information



pewag

Lifting Point PLZW Zeta can be assembled and disassembled without tools (Up to thread size M24). The lifting point allows full 360° rotation, comes with five-fold security against breakage and can be loaded in all directions.

The PLZW Zeta protects the surface of the load from damage by integrating a sleeve. The replaceable bolt is 100% crack tested and has a chrome-VI-free corrosion protection as well as a marking with load capacity, thread size and tightening torque.

PLZW, is easily dismountable without the use of tools and is designed for quick and effortless disassembly into its individual parts. This special feature enables the direct assembly of various fittings (such as round slings, webbing slings, wire rope eyes, master links, and eye-type hooks) without having to use an additional shackle or connection link. It is distinguished by a golden-colored sleeve

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, thread size and an individual serial number.


Temperature range: -20 °C to +200 °C

Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1

Lifting Point Pewag PLZW Zeta

Blueprint



Technical data

Part code	Code	WLL ton	Thread mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	n mm mm	n max mm mm	Weight kg
42154105521	PLZW 0,4T	0.4	M8x12	40	64	29	14	34	30	77	12	80	0.3
42154105522	PLZW 0,63T	0.63	M10x15	40	64	29	14	34	30	77	15	100	0.3
42154126563	PLZW 0,95T	0.95	M12x18	40	64	29	14	34	30	77	18	180	0.3
42154105524	PLZW 1,8T	1.8	M16x24	50	83	43	19	50	45	112	24	260	0.9
42154105525	PLZW 2,5T	2.5	M20x30	50	83	43	19	50	45	112	30	330	0.95
42154105526	PLZW 4T	4	M24x36	70	121	64	28	69	68	161	36	355	2.8
42154091997	PLZW-FIX 6,3T	6.3	M30	70	121	64	28	69	68	161	45	355	3
42154091624	PLZW-FIX 10T	10	M36	110	183	106	38	114	108	259	59	328	10.8
42154091625	PLZW-FIX 13T	13	M42	110	183	106	38	114	108	259	69	328	11.1
42154091626	PLZW-FIX 15T	15	M48	110	183	106	38	114	108	259	74	328	11.2