

Lifting Point Pewag PLZW-FIX-SP Zeta

Product information



Lifting Point PLZW-FIX-SP is rotatable by 360° and may be loaded in all directions. The PLZW protects the surface of the load from damage thanks to an integrated sleeve. The screw is 100% crack-tested, comes with a chromate VI-free protection against corrosion.

PLZW-FIX-SP is non-dismountable, but includes a spring that ensures the ring stays in its position. It is identified by a grey sleeve.

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, thread size and an individual serial number.


Temperature range: -20 °C to +200 °C

Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1

Lifting Point Pewag PLZW-FIX-SP Zeta

Blueprint



Technical data

Part code	Code	WLL ton	Thread mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	h mm mm	n mm mm	n max mm mm
42154092941	PLZW-FIX-SP 0,4T	0.4	M8	40	64	14	34	77	30	29	12	80
42154092943	PLZW-FIX-SP 0,63T	0.63	M10	40	64	14	34	77	30	29	15	100
42154093204	PLZW-FIX-SP 0,95T	0.95	M12	40	64	14	34	77	30	29	18	180
42154096423	PLZW-FIX-SP 1,8T	1.8	M16	50	83	19	50	112	45	43	24	260
42154096424	PLZW-FIX-SP 2,5T	2.5	M20	50	83	19	50	112	45	43	30	330
42154012816	PLZW-FIX-SP 4T	4	M24	70	121	28	69	161	68	64	36	355
42154091998	PLZW-FIX-SP 6,3T	6.3	M30	70	121	28	69	161	68	64	45	355
42154093894	PLZW-FIX-SP 10T	10	M36	110	183	38	114	259	108	106	59	328
42154093895	PLZW-FIX-SP 13T	13	M42	110	183	38	114	259	108	106	69	328
42154093896	PLZW-FIX-SP 15T	15	M48	110	183	38	114	259	108	106	74	328