

## Hand spurgear winch MANIBOX GR, Painted

---

### Product information



Hand spurgear winches from 300 to 2750 kg for daily use.

#### Applications:

- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers

#### Technical properties:

- Compact and rugged construction with steel frame.
- Machined parts.
- Steel or cast iron drum depending on models.
- Flat mounted or wall mounted positions for GR 300/530/500.
- 4 fixation points.
- Fully protected gear system.
- Removable crank positioned on the left hand side for the GR 300/530/500/750 and on the right hand side for the GR 1000/1450/2000/2750.
- Free spooling drum, only when not in load.
- Composite material automatic brake. - Failsafe system for correct rope winding direction (patented)

#### Optional:

Wire rope and hook.

[... Read more](#)

---

**Marking:** According to standard, CE-marked


**Temperature range:** -10°C up to +50°C

**Finish:** Painted

**Standard:** EN 13157

## Hand spurgear winch MANIBOX GR, Painted

### Blueprint



### Technical data

| Part code       | WLL ton | Rope Ø mm | Capacity 1st layer kg | Number of layers | Lift per crank revolution mm | Hand force max. kg | Max. drum capacity m | Drum Ø mm | A mm | B mm | C mm | D mm | E mm | F mm | G mm | K mm | Lg mm | S mm | T mm | Weight kg |
|-----------------|---------|-----------|-----------------------|------------------|------------------------------|--------------------|----------------------|-----------|------|------|------|------|------|------|------|------|-------|------|------|-----------|
| 501300030000140 | 0.3     | 5         | 500                   | 6                | 30.5                         | 12.6               | 38                   | 62        | 249  | 400  | 190  | 217  | 240  | 200  | 145  | 144  | 122   | 184  | 76   | 15        |
| 501300050000140 | 0.5     | 7         | 750                   | 4                | 31.5                         | 12.5               | 18                   | 62        | 249  | 400  | 190  | 217  | 240  | 200  | 145  | 144  | 122   | 184  | 76   | 15        |
| 501300530000140 | 0.53    | 6         | 530                   | 1                | 30.5                         | 12.5               | 4                    | 62        | 249  | 400  | 190  | 217  | 240  | 200  | 145  | 144  | 122   | 184  | 76   | 15        |
| 501300750000140 | 0.75    | 7         | 750                   | 1                | 31.5                         | 19                 | 3                    | 62        | 249  | 400  | 190  | 217  | 240  | 200  | -    | 144  | 122   | -    | -    | 15        |
| 501300100000140 | 1       | 9         | 1,450                 | 4                | 16                           | 14.5               | 30                   | 103.5     | 410  | 485  | 305  | 300  | 340  | 370  | -    | 236  | 176   | -    | -    | 44        |
| 501300150000140 | 1.45    | 10        | 1,450                 | 1                | 16                           | 14.5               | 5                    | 103.5     | 410  | 485  | 305  | 300  | 340  | 370  | -    | 236  | 176   | -    | -    | 44        |
| 501300200000140 | 2       | 13        | 2,750                 | 3                | 9.5                          | 16.5               | 25                   | 121       | 510  | 585  | 360  | 400  | 340  | 440  | -    | 325  | 237.5 | -    | -    | 83        |
| 501300280000140 | 2.75    | 13        | 2,750                 | 1                | 9.5                          | 16.5               | 6                    | 121       | 510  | 585  | 360  | 400  | 340  | 440  | -    | 325  | 237.5 | -    | -    | 83        |