

Hand spurgear winch MANIBOX GR, Stainless Steel Finish

Product information



Hand spurgear winches from 300 to 2750 kg for daily use.

Applications:

- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers

Technical properties:

- Compact and rugged construction with steel frame.
- Machined parts.
- Steel or cast iron drum depending on models.
- Flat mounted or wall mounted positions for GR 300/530/500.
- 4 fixation points.
- Fully protected gear system.
- Removable crank positioned on the left hand side for the GR 300/530/500/750 and on the right hand side for the GR 1000/1450/2000/2750.
- Free spooling drum, only when not in load.
- Composite material automatic brake. - Failsafe system for correct rope winding direction (patented)

Optional:

Wire rope and hook.

[... Read more](#)

Marking: According to standard


Temperature range: -10°C to +50°C

Finish: Stainless steel

Standard: EN 13157

Hand spurgear winch MANIBOX GR, Stainless Steel Finish

Blueprint



Technical data

| Part code | Code | WLL ton | Rope Ø mm | Capacity 1st layer kg | Number of layers | Lift per crank revolution mm | Max. crank effort kg | Max. drum capacity m | A mm | B mm | C mm | D mm | E mm | F mm | G mm | K mm | S mm | T mm | Weight |
|-----------------|--------|---------|-----------|-----------------------|------------------|------------------------------|----------------------|----------------------|------|------|------|------|------|------|------|------|------|------|--------|
| 501300030000650 | GR300 | 0.3 | 5 | 500 | 6 | 30.5 | 12.5 | 38 | 249 | 400 | 190 | 217 | 240 | 200 | 145 | 144 | 184 | 76 | 15 |
| 501300050000650 | GR500 | 0.5 | 7 | 750 | 4 | 31.5 | 19 | 18 | 249 | 400 | 190 | 217 | 240 | 200 | 145 | 144 | 184 | 76 | 15 |
| 501300053000650 | GR530 | 0.53 | 6 | 530 | 1 | 30.5 | 12.5 | 4 | 249 | 400 | 190 | 217 | 240 | 200 | 145 | 144 | 184 | 76 | 15 |
| 501300080000650 | GR750 | 0.75 | 7 | 750 | 1 | 31.5 | 19 | 3 | 249 | 400 | 190 | 217 | 240 | 200 | - | 144 | - | - | 15 |
| 501300100000650 | GR1000 | 1 | 9 | 1,450 | 4 | 16 | 14.5 | 30 | 410 | 485 | 305 | 300 | 340 | 370 | - | 236 | - | - | 44 |
| 501300150000650 | GR1450 | 1.45 | 10 | 1,450 | 1 | 16 | 14.5 | 5 | 410 | 485 | 305 | 300 | 340 | 370 | - | 236 | - | - | 44 |
| 501300200000650 | GR2000 | 2 | 13 | 2,750 | 3 | 9.5 | 16.5 | 25 | 510 | 585 | 360 | 400 | 340 | 440 | - | 325 | - | - | 83 |
| 501300260000650 | GR2750 | 2.57 | 13 | 2,750 | 1 | 9.5 | 16.5 | 6 | 510 | 585 | 360 | 400 | 340 | 440 | - | 325 | - | - | 83 |