

Hand spurgear winch MANIBOX GR, Stainless Steel Finish



Product information

Hand spurgear winches from 300 to 2750 kg for daily use.

Applications:

- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers

Technical properties:

- Compact and rugged construction with steel frame.
- Machined parts.
- Steel or cast iron drum depending on models.
- Flat mounted or wall mounted positions for GR 300/530/500.
- 4 fixation points.
- Fully protected gear system.
- Removable crank positioned on the left hand side for the GR 300/530/500/750 and on the right hand side for the GR 1000/1450/2000/2750.
- Free spooling drum, only when not in load.
- Composite material automatic brake. - Failsafe system for correct rope winding direction (patented)

Optional:

Wire rope and hook.

Marking: According to standard

Temperature range: -10°C to +50°C

Finish: Stainless steel

Standard: EN 13157

Part code	Code	WLL ton	Rope Ø mm	Capacity 1st layer kg	Number of layers	Lift per crank revolution mm	Max. crank effort kg	Max. drum capacity m	A mm	B mm	C mm	D mm	E mm	F mm	G mm	K mm	S mm	T mm	Weight
501300030000650	GR300	0.3	5	500	6	30.5	12.5	38	249	400	190	217	240	200	145	144	184	76	15
501300050000650	GR500	0.5	7	750	4	31.5	19	18	249	400	190	217	240	200	145	144	184	76	15
501300053000650	GR530	0.53	6	530	1	30.5	12.5	4	249	400	190	217	240	200	145	144	184	76	15
501300080000650	GR750	0.75	7	750	1	31.5	19	3	249	400	190	217	240	200	-	144	-	-	15
501300100000650	GR1000	1	9	1,450	4	16	14.5	30	410	485	305	300	340	370	-	236	-	-	44
501300150000650	GR1450	1.45	10	1,450	1	16	14.5	5	410	485	305	300	340	370	-	236	-	-	44
501300200000650	GR2000	2	13	2,750	3	9.5	16.5	25	510	585	360	400	340	440	-	325	-	-	83
501300260000650	GR2750	2.57	13	2,750	1	9.5	16.5	6	510	585	360	400	340	440	-	325	-	-	83

Blueprint

