

Hand spurgear Winch SS TIREX



Product information

Hand spurgear winch in compact design available in 150 and 300 kg, stainless steel model (with stainless steel mounting plate).

Suitable for moderate use both indoor and outdoor.

Applications:

- Lifting of doors
- Opening of hatches
- Moving a boat
- Scenery handling
- Lifting equipment

Technical properties:

- Chassis made of an aluminum frame.
- Composite drum.
- Planetary reducer
- Mounting plate in galvanised steel (standard model) or in 316L anti-corrosion stainless steel (stainless steel model).
- Flat mounted.
- 4 fixation points.
- Removable crank.
- Free spooling drum, only when not in load.
- Automatic brake in composite material.
- Failsafe system for correct rope winding direction (patented).

Options: Stainless steel Wire rope and hook or Fibre rope and Stainlesssteel hook.

Material: Stainless steel

Marking: According to standard, CE-marked

Temperature range: -10°C to +50°C

Standard: EN 13157

Part code	WLL ton	Model	Rope Ø mm	WLL top layer ton	Number of layers	Lift per crank revolution mm	Hand force max. kg	Max. drum capacity m	Weight kg
501300030000450	0.25	TIREX150INOX	4	0.15	6	40	8	24	3.7
501300040000450	0.4	TIREX300INOX	5	0.3	3	41	14	8.5	3.7

Blueprint

