Beam Anchor 3M DBI-SALA 2108412 – 21084015

Product information



The 3M™ DBI-SALA® beam clamp for use on steel H-beams. This system provides a high-quality anchorage point. It is designed to offer ease of use and deliver exceptional safety and performance for your fall protection system.

3 Acceptable orientations for Installation:

- top flange
- bottom flange
- side flange (if the profile is installed in this way).

Applications:
Recommended for use in construction, general industry, mining, oil and gas, transport, utilities and wind energy sectors.

Advantages:

- Compatible with various fall protection systems
- Compact, lightweight design
- Easy to assemble and disassemble.
- Quick to adjust to the correct size.
- Ideal for use with personal fall protection systems with self-retracting lines - fall arrest blocks
- pivoting connection with D-ring
- Portable and reusable
- Corrosion-resistant construction for durability

... *Read more*

Material: Alloy Steel - Aluminum alloy
Marking: According to standard, CE-mark
Temperature range: -40°C to +60°C
Finish: Galvanized
Standard: EN 795-B

© November 2026 - All Rights Reserved

Beam Anchor 3M DBI-SALA 2108412 – 21084015

Technical data

Size	Max user weight kg	Max flange thickness mm	Flange width mm	Weight kg
S-M	140	38	63.5 - 304.8	2.4
M-L	140	38	63.5 - 457.2	2.7
L-XL	140	38	63.5 - 609.6	3
XL-XXL	140	38	304.8 - 914.4	4

© November 2026 - All Rights Reserved