Coupling Link Gunnebo, G Grabiq

Product information



For use with master link and eye hook.

... Read more

Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated.

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Coupling Link Gunnebo, G Grabiq

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	F mm	L mm	Weight kg
402200150090	G-6-10	6	1.5	8	15	16	7	45	0.1
402200200090	G-7-10	7	2	11	18	22	9	56	0.2
402200260090	G-8-10	8	2.6	11	18	22	9	56	0.2
402200400090	G-10-10	10	4	13	25	26	12	68	0.3
402200680090	G-13-10	13	6.8	17	29	33	15	89	0.7
402201030090	G-16-10	16	10.3	20	36	40	19	106	1.4
402201600090	G-20-10	20	16	26	43	44	23	125	2.2
402202000090	G-22-10	22	20	28	50	59	26	152	3.6
402202730090	G-26-10	26	27.3	34	58	61	32	161	5.7
402204000090	G-32-10	32	40	40	70	77	38	200	9.5

© November 2026 - All Rights Reserved